







	ŧU	t 1,499	£ 2,349
PRODUCT INFORMATION			
			We reserve the right to modify the information of
			the products that appear on this website withou
NOTE	-	-	prior notice, including equipment, specifications,
			models, colors and materials
FRAME SIZES	M (50cm)	M (52cm) - L (56cm)	M (50cm) - L (56cm)
WEIGHT	Approx. 27 Kg	Approx. 20kg	Approx. 27kg
MAXIMUM BIKE & RIDER WEIGHT	120Kg	150kg	120kg
		Powder painting scratch resistant with Glossy	12 ong
PAINTING	Powder Painting Scratch Resistant with Matte	Varnish	-
201 0110()			White Star with glossy varnish Happy Blue with
COLOUR(s)	Black Suit with Matte Finish	Metallic Blue	matte finish Black Suit with matte finish
FRAME			
FRAME	Aluminium High Step	Aluminium High Step	Aluminium High Step
SUSPENSION	Sr SUNTOUR Mobie E25 Air 75mm		
FORK	31 3011 OOK Ploble E23 All 73HHT	Rigid Alloy 28"	Rigid Alloy 28"
	- FC & 1 FILE 1 1/01 To report CLUC		
HEADSET	FSA 1.5" to 1-1/8" Tapered SHIS	Semi integrated 1-1/8"	FSA 1.5" to 1-1/8" Tapered SHIS
E-BIKE SYSTEM			
DRIVE UNIT	BROSE DRIVE S ALU 90Nm	BAFANG H400B Rear Wheel 45Nm	BROSE DRIVE S ALU 90Nm
BATTERY	504Wh 36V - Semi-integrated on Downtube -	36V 360Wh - Integrated on Downtube - Non	504Wh 36V - Semi-integrated on Downtube -
DALLERT	Removable	Removable	Removable
RANGE	40km to 100km	40km to 100km	40km to 100km
BATTERY LOCK KEY	Yes	-	Yes
CHARGER	4A - 3 to 6 hours total charge time	2A - 5 hours total charge time	4A - 3 to 6 hours total charge time
DISPLAY	BROSE Allround	BAFANG DP.C11	BROSE Allround
СОСКРІТ			
	AL 550 (21 0 (5t inlat)	70014 000001 / 000000 / 21 00000 / 51 000 250	Al (200 - 121 0 - 125 -
HANDLEBAR	AL 660mm / 31.8mm (Straight)	Z00M Gravel 400mm / 31.8mm / Flare 25°	AL 680mm / 31.8mm (Straight)
STEM	AL 90mm - 31.8mm - adjustable 0-90°	AL 100mm - 31.8mm - 7º	AL 90mm - 31.8mm - adjustable 0-90°
GRIPS	ERGON GA30	SELLE ITALIA SG Tape	ERGON GA30
WHEELSET			
TYRES	CONTINENTAL Double Fighter III 29''x2,0''	VITTORIA Terreno Dry 29"x1,75"	CONTINENTAL Double Fighter III 29"x2,0"
WHEEL SIZE	29"	29"	29"
RIMS	Alloy Double Wall 25mm	Alloy Double Wall 25mm	Alloy Double Wall 25mm
SPOKES	Black Stainless Steel	Stainless Steel	Black Stainless Steel
FRONT HUB	SHIMANO HB-MT400 100 Thru Axle 15mm	Alloy 9x135mm QR	SHIMANO HB-MT400 100 Thru-axle 15mm
REAR HUB	SHIMANO Deore M6000 135mm	BAFANG H400B 135mm	SHIMANO Deore M6000 135mm
DRIVETRAIN & BRAKES	G. III. II. II. G. G. G. F. 1. G. G. G. Z. G.	5, 11, 11, 10, 11, 10, 10, 10, 11, 11, 11	51111 17 11 10 D GGI G 1 10 GG G 25 G 11 11 11
	SUBMINIST L. L. ATTOO	TEKTRO O LL A S' A LL A L' LID OTOS	SUNANDA L. II. MTOO
BRAKES	SHIMANO Hydraulic MT200	TEKTRO Cable Activated Hydraulic HD-C705	SHIMANO Hydraulic MT200
BRAKE ROTOR - Front	SHIMANO SM-RT10 180mm	SHIMANO SM-RT26 180mm	SHIMANO SM-RT10 180mm
BRAKE ROTOR - Rear	SHIMANO SM-RT10 180mm	SHIMANO SM-RT26 180mm	SHIMANO SM-RT10 180mm
REAR DERRAILEUR	SHIMANO Deore 10S	MICROSHIFT AdventX 10S	SHIMANO Deore 10S
CASSETTE	SHIMANO Deore 10S 11-42T	MICROSHIFT AdventX 10S 11-48T	SHIMANO Deore 10S 11-42T
SHIFTERS	SHIMANO Deore 10S	MICROSHIFT AdventX 10S	SHIMANO Deore 10S
CHAINRING	SAMOX BCD 104 36T	MIRANDA ChainFlow BCD104 38T	SAMOX BCD 104 36T
CRANK	SAMOX Shape 175/0	MIRANDA JIS 170	SAMOX Shape 175/0
CHAIN	SHIMANO CN-E6090 10S E-Bike	KMC e10 Turbo e-bike series	SHIMANO CN-E6090
CHAINGUARD	Yes - FSA	Yes - MIRANDA	Yes - FSA
SAFETY & ACESSORIES			
RACK	ATRANVELO Tour AVS (max.: 25Kg)		ATRANVELO Tour AVS (max.: 25Kg)
FRONT LIGHT	AXA Blueline 30 with reflector	_	AXA Blueline 30 with reflector
	AXA Slim with reflector		PICCADILLY with reflector
REAR LIGHT		-	
KICKSTAND	ATRANVELO Dux	-	ATRANVELO Dux
MUDGUARD	SKS	-	SKS
BELL	Yes	-	Yes
	Not included. Sold separately.	Not included. Sold separately.	Not included. Sold separately.
		SELLE ITALIA A LAVO (I	
BOTTLE CAGE SADDLE	SELLE ROYAL Essenza Moderate Gel	SELLE ITALIA Model X Superflow	SELLE ROYAL Essenza Moderate Gel
SADDLE	SELLE ROYAL Essenza Moderate Gel AL Black 350mm 31,6mm/15mm	AL Black 300mm 31,6mm /15mm	AL Black 350mm 31,6mm/15mm
SADDLE SEAT POST		·	
	AL Black 350mm 31,6mm/15mm	AL Black 300mm 31,6mm /15mm	AL Black 350mm 31,6mm/15mm

^{*} We reserve the right to modify product information that appears on this website without prior notice, including equipment, specifications, models, colors and materials.