



E900 Crossover
€ 2,999



C800 Trekking
€ 2,199



C500 Trekking
€ 1,299



C800 Trekking Suspension
€ 0

PRODUCT INFORMATION

NOTE	-	We reserve the right to modify the information of the products that appear on this website without prior notice, including equipment, specifications, models, colors and materials		-	-
FRAME SIZES	S (44cm) - M (49cm) - L (54cm)	M (50cm) - L (56cm)	M (19cm) - L (20,5cm)	M (50cm)	
WEIGHT	Approx. 28kg	Approx. 27kg	Approx. 25kg	Approx. 27 Kg	
MAXIMUM BIKE & RIDER WEIGHT	190Kg	120kg	120kg	120Kg	
PAINTING	Powder Painting Scratch Resistant with Matte or Glossy Varnish	-	-	Powder Painting Scratch Resistant with Matte	
COLOUR(s)	Hock Grey with matte finish Dark Olive with matte finish Light Nude with matte finish	White Star with glossy varnish Happy Blue with matte finish Black Suit with matte finish	White Star with glossy finish Happy Blue with matte finish Black Suit with matte finish	Black Suit with Matte Finish	

FRAME

FRAME	Low Step Aluminium	Aluminium High Step	Aluminium High Step	Aluminium High Step	
SUSPENSION	Sr Suntour Raindon 34 Air Travel 120mm Axle Boost 110mm 27,5"	-	-	Sr SUNTOUR Mobie E25 Air 75mm	
FORK	-	Rigid Alloy 28"	Rigid Alloy 28"	-	
HEADSET	FSA 1.5" to 1-1/8" Tapered SHIS	FSA 1.5" to 1-1/8" Tapered SHIS	ACROS 1.5" to 1-1/8" Tapered SHIS	FSA 1.5" to 1-1/8" Tapered SHIS	

E-BIKE SYSTEM

DRIVE UNIT	BROSE DRIVE S MAG Horizontal 90Nm	BROSE DRIVE S ALU 90Nm	SHIMANO Steps E5000 Horizontal 40Nm	BROSE DRIVE S ALU 90Nm	
BATTERY	522Wh 36V - Down Tube Integration - Removable	504Wh 36V - Semi-integrated on Downtube - Removable	418Wh 36V - Semi-integrated on Downtube - Removable	504Wh 36V - Semi-integrated on Downtube - Removable	
RANGE	40km to 100km	40km to 100km	40km to 100km	40km to 100km	
BATTERY LOCK KEY	Yes	Yes	Yes	Yes	
CHARGER	4A - 3 to 6 hours total charge time	4A - 3 to 6 hours total charge time	2A - 6 hours total charge time	4A - 3 to 6 hours total charge time	
DISPLAY	BROSE Allround	BROSE Allround	SHIMANO E5000	BROSE Allround	

COCKPIT

HANDLEBAR	AL 780mm / 31.8mm / Rise 20mm (Straight)	AL 680mm / 31.8mm (Straight)	AL 660mm / 31.8mm (Straight)	AL 660mm / 31.8mm
-----------	--	------------------------------	------------------------------	-------------------