









NOTE NOTE NOTE NOTE NOTE NOTE NOTE NOTE	Downtube - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm - adjustable 0-
NOTE NOTE NOTE NOTE NOTE NOTE NOTE NOTE	information of the products that appear on this website without prior notice, including equipment, specifications, models, colors and materials M (50cm) - L (56cm) Approx. 27kg 120kg - White Star with glossy varnish Happ Blue with matte finish Black Suit with matter finish Black Suit with matte
NOTE FRAME SIZES \$ (44cm) - M (49cm) - L (54cm) Approx. 28kg Approx	information of the products that appear on this website without prior notice, including equipment, specifications, models, colors and materials M (50cm) - L (56cm) Approx. 27kg 120kg - White Star with glossy varnish Happ Blue with matte finish Black Suit with matter finish Black Suit with matte
FRAME SIZES S. (44cm) - M. (49cm) - L. (54cm) S-M. (42cm) - L. /3L. (46cm) M. (52cm) - L. (56cm) M. MECHT Approx. 28kg Approx	notice, including equipment, specifications, models, colors and materials M (50cm) - L (56cm) Approx. 27kg 120kg - White Star with glossy varnish Happ Blue with matte finish Black Suit with matte finish Black Suit with matte finish Aluminium High Step - Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm 504Wh 36V - Semi-integrated on Downtube - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm (Straight)
RRAME SIZES S. (A4cm) - M. (49cm) - L. (54cm) S-M. (42cm) - L. (24cm) M. (52cm) - L. (56cm) M. MEIGHT Approx. 28kg	specifications, models, colors and materials M (50cm) - L (56cm) Approx. 27kg 120kg - White Star with glossy varnish Happ' Blue with matte finish Black Suit with matte finish Black Suit with matte finish Aluminium High Step - Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm 504Wh 36V - Semi-integrated on Downtube - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm - adjustable 0-
Park	materials M (50cm) - L (56cm) Approx. 27kg 120kg - White Star with glossy varnish Happ Blue with matte finish Black Suit with matte finish Aluminium High Step - Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm 504Wh 36V - Semi-integrated on Downtube - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm - adjustable 0-
FRAME Law Step Aluminium	M (50cm) - L (56cm) Approx. 27kg 120kg - White Star with glossy varnish Happ Blue with matte finish Black Suit with matte finish Aluminium High Step - Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm 504Wh 36V - Semi-integrated on Downtube - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm - adjustable 0-
MAXIMUM BIKE & RIDER WEIGHT Approx. 28kg Approx. 26kg Approx. 20kg Appr	Approx. 27kg 120kg - White Star with glossy varnish Happ Blue with matte finish Black Suit with matte finish Aluminium High Step - Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm 504Wh 36V - Semi-integrated on Downtube - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm - adjustable 0-
MAXIMUM BIKE & RIDER WEIGHT 190Kg 135Kg 150kg 12	20kg White Star with glossy varnish Happ Blue with matte finish Black Suit with matte finish Black Suit with matte finish Aluminium High Step Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90NM 504Wh 36V - Semi-integrated on Downtube - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm - adjustable 0-
PAINTING With Matter of Clossy Varnish with Matter of Clossy Varnish with Matter of Clossy Varnish with Matter (Clossy Varnish With Matter Var	- White Star with glossy varnish Happ Blue with matte finish Black Suit with matte finish Black Suit with matte finish Aluminium High Step - Rigid Alloy 28" FSA 15" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm 504Wh 36V - Semi-integrated on Downtube - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm (Straight)
#ANNING with Matter of lossy Varnish Hock Grey with matter finish Dark Olive with matter fin	Blue with matte finish Black Suit with matte finish Aluminium High Step - Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm 504Wh 36V - Semi-integrated on Downtube - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm - adjustable 0-
Mock Grey with matte finish Light Nude Mock Grey with matte finish Light Nude with matter	Blue with matte finish Black Suit with matte finish Aluminium High Step - Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm 504Wh 36V - Semi-integrated on Downtube - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm - adjustable 0-
COLOUR(s) Olive with matte finish Light Nude with matte finish Light Nume with matter finish	Blue with matte finish Black Suit with matte finish Aluminium High Step - Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm 504Wh 36V - Semi-integrated on Downtube - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm - adjustable 0-
FRAME	matte finish Aluminium High Step - Rigid Alloy 28" FSA 15" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm 504Wh 36V - Semi-integrated on Downtube - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm - adjustable 0-
FRAME Low Step Aluminium MTB Hardtail Aluminium Aluminium High Step Al SUSPENSION Sr Suntour Raindon 34 Air Travel 120mm Axle Boost 110mm 27.5" Rockshox 35S Air Travel 120mm Axle Boost 110mm 27.5" Rockshox 35S Air Travel 120mm Axle Boost 110mm 27.5" Rigid Alloy 28" RI FORK - A. 15" to 1-1/8" Tapered SHIS FSA 15" to 1-1/8" Tapered SHIS Semi integrated 1-1/8" RI FEBIKE SYSTEM BROSE DRIVE S MAG Horizontal 90Nm BAFANG H4008 Rear Wheel 45Nm BI BATTERY RROSE DRIVE S MAG Horizontal 90Nm BAFANG H4008 Rear Wheel 45Nm BI BANDE 40km to 100km 40km to 100km 36V 360Wh - Integrated on Downtube SQW 36V 360Wh - Integrated on Downtube Removable 40km to 100km 44 BATTERY \$22Wh 36V - Down Tube Integration - Removable - Non Removable - Non Removable 40km to 100km 44 BATTERY LDCK KEY Yes Yes - Shours total charge time A-3 to 6 hours total charge time 4A -3 to 6 hours total charge time 5K Alfound 4A -3 to 6 hours total charge time 5K Alfound 5	Aluminium High Step - Rigid Alloy 28" FSA 15" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm 504Wh 36V - Semi-integrated on Downtube - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm - adjustable 0-
FRAME	Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90NM 504Wh 36V - Semi-integrated on Downtube - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm - adjustable 0-
Sr Suntour Raindon 34 Air Travel Rockshox 35S Air Travel 120mm Axle Boost 110mm 27.5" Rockshox 35S Air Travel 120mm Axle Boost 110mm 27.5"/29" Rigid Alloy 28" Right	Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90NM 504Wh 36V - Semi-integrated on Downtube - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm - adjustable 0-
Sr Suntour Raindon 34 Air Travel Rockshox 35S Air Travel 120mm Axle Boost 110mm 27.5" Rockshox 35S Air Travel 120mm Axle Boost 110mm 27.5"/29" Rigid Alloy 28" Right	Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90NM 504Wh 36V - Semi-integrated on Downtube - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm - adjustable 0-
120mm Axle Boost 110mm 27.5" Boost 110mm 27.5" Scott 110mm 27.5" Core Rigid Alloy 28" Rigi	FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90NM 504Wh 36V - Semi-integrated on Downtube - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm - adjustable 0-
FSA 1.5" to 1-1/8" Tapered SHIS FSA 1.5" to 1-1/8" Tapered SHIS FSA 1.5" to 1-1/8" Tapered SHIS FSEBIKE SYSTEM	FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90NM 504Wh 36V - Semi-integrated on Downtube - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm - adjustable 0-
FSA 1.5" to 1-1/8" Tapered SHIS FSA 1.5" to 1-1/8" Tapered SHIS FSA 1.5" to 1-1/8" Tapered SHIS FSEBIKE SYSTEM	FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90NM 504Wh 36V - Semi-integrated on Downtube - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm - adjustable 0-
E-BIKE SYSTEM DRIVE UNIT BROSE DRIVE S MAG Horizontal 90Nm BROSE DRIVE S MAG Horizontal 90Nm BAFANG H400B Rear Wheel 45Nm BI BATTERY 522Wh 36V - Down Tube Integration - Removable 522Wh 36V - Integrated on Downtube - Removable 36V 360Wh - Integrated on Downtube - Non Removable 50 RANGE 40km to 100km 40km to	BROSE DRIVE S ALU 90Nm 504Wh 36V - Semi-integrated on Downtube - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm - adjustable 0-
DRIVE UNIT BROSE DRIVE S MAG Horizontal 90Nm BROSE DRIVE S MAG Horizontal 90Nm BAFANG H400B Rear Wheel 45Nm BIBATTERY BATTERY 522Wh 36V - Down Tube Integration - Removable 522Wh 36V - Integrated on Downtube - Removable 36V 360Wh - Integrated on Downtube - Non Removable 36V 360Wh - Integrated on Downtube - Non Removable 522Wh 36V - Integrated on Downtube - Removable 36V 360Wh - Integrated on Downtube - Non Removable 40Wm to 100Wm 44 RANGE 40km to 100km 40km to 100km 40km to 100km 44 BATTERY LOCK KEY Yes - Yes - Yes CHARGER 4A - 3 to 6 hours total charge time 4A - 3,6 hours total charge time 2A - 5 hours total charge time 4A DISPLAY BROSE Allround BROSE Allround BAFANG DPC11 BIB COCKPIT HANDLEBAR AL 780mm / 31.8mm / Rise 20mm (Straight) FSA V-Drive 740mm / 31.8mm 25° AL STEM AL 50mm - 31.8mm - 0° FSA V-Drive 60mm/ 31.8mm / ±6° AL 100mm - 31.8mm - 7° Al GRIPS ERGON GA30 SELLE ITALIA SG Tape EI WHEELST	504Wh 36V - Semi-integrated on Downtube - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm - adjustable 0-
BATTERY 522Wh 36V - Down Tube Integration - Removable - Removable - Removable - Removable - Removable - Removable - Non Removable - No	504Wh 36V - Semi-integrated on Downtube - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm - adjustable 0-
BATTERY Removable - Removable - Non Removable D RANGE 40km to 100km 40km to 100km 40km to 100km 44km to 100km 4km to 100km 44km to 100km 4km to 10km to 10km <td< td=""><td>Downtube - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm - adjustable 0-</td></td<>	Downtube - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm - adjustable 0-
Removable - Removable - Non Removable Non Removable - Non Removable Non Re	40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm - adjustable 0-
BATTERY LOCK KEY Yes Yes - Yes CHARGER 4A - 3 to 6 hours total charge time 4A - 3,6 hours total charge time 2A - 5 hours total charge time 4A DISPLAY BROSE Allround BROSE Allround BAFANG DP.C11 BI COCKPIT HANDLEBAR AL 780mm / 31.8mm / Rise 20mm (Straight) FSA V-Drive 740mm / 31.8mm Z00M Gravel 400mm / 31.8mm / Flare 25° AL 50mm - 31.8mm - 70° AL 50mm - 31.8mm - 70° AL 100mm	Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm - adjustable 0-
CHARGER 4A - 3 to 6 hours total charge time 4A - 3,6 hours total charge time 2A - 5 hours total charge time 4A - 3 to 6 hours total charge time 4A - 3,6 hours total charge time 4A - 5,6 hours total charge time 4A - 3,6 hours total charge times 4A - 3,6 hours total charge times	4A - 3 to 6 hours total charge time BROSE Allround AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm - adjustable 0-
DISPLAY BROSE Allround BROSE Allround BAFANG DP.C11 BI COCKPIT HANDLEBAR AL 780mm / 31.8mm / Rise 20mm (Straight) FSA V-Drive 740mm / 31.8mm / 25° AL 780mm / 31.8mm / FIare 25° AL 780mm / 31.8mm / FIARE 25° AL 780mm / 31.8mm / 25° AL 100mm - 31.8mm / 7° AL 780mm / 31.8mm / 25° AL 100mm - 31.8mm / 7° AL 780mm - 31.8mm - 7° AL 780mm - 275" x2,6" / M - L/XL) 29" AL 780mm - 29"	BROSE Allround AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm - adjustable 0-
COCKPIT HANDLEBAR AL 780mm / 31.8mm / Rise 20mm (Straight) STEM AL 50mm - 31.8mm - 0° FSA V-Drive 740mm / 31.8mm Z500M Gravel 400mm / 31.8mm / Flare AL 55° AL 100mm - 31.8mm - 7° AL 50mm - 31.8mm - 0° FSA V-Drive 60mm / 31.8mm / ±6° AL 100mm - 31.8mm - 7° AL 50mm - 31.8mm - 7° AL 50mm - 31.8mm - 0° FSA V-Drive 60mm / 31.8mm / ±6° AL 100mm - 31.8mm - 7° AL 50mm - 31.8mm - 7° AL 50mm - 31.8mm - 7° AL 50mm - 31.8mm - 7° AL 100mm - 31.8mm / 100mm - 31.8mm - 7° AL 100mm - 31.8mm / 100mm - 31.8mm / 100mm / 10	AL 680mm / 31.8mm (Straight) AL 90mm - 31.8mm - adjustable 0-
HANDLEBAR	AL 90mm - 31.8mm - adjustable 0-
AL 50mm - 31.8mm - 0°	AL 90mm - 31.8mm - adjustable 0-
AL 50mm - 31.8mm - 0°	AL 90mm - 31.8mm - adjustable 0-
STEM AL 50mm - 31.8mm - 0° FSA V-Drive 60mm/ 31.8mm / ±6° AL 100mm - 31.8mm - 7° AA 90 90 90 90 90 90 90 90 90 90 90 90 90	-
GRIPS ERGON GA30 ERGON GA30 SELLE ITALIA SG Tape EI WHEELSET TYRES CONTINENTAL Mountain king MAXXIS Rekon S - 27,5"x2,6" / M - L/XL-29"x2,4" VITTORIA Terreno Dry 29"x1,75" 29"x2,4" VITTORIA Terreno Dry 29"x1,75" 29"x2,4" 29"x2,6" (Tubeless Ready) 29"x2,4" 29"x1,75" 29"x2,4" 29"x2,4"x2,4" 29"x2,4" 29"x2,4"x2,4" 29"x2,4"x2,4"x2,4"x2,4"x2,4"x2,4"x2,4"x2,4	-
WHEELSET TYRES CONTINENTAL Mountain king 27,5"x2,6" (Tubeless Ready) MAXXIS Rekon S - 27,5"x2,6" (M - L/XL 29"x2,4" VITTORIA Terreno Dry 29"x1,75" CI 29"x2,4" WHEEL SIZE 27,5" 27,5" (S) / 29" (M-L/XL) 29" 29" RIMS Alloy Double Wall 30mm (Tubeless Ready) Alloy Double Wall 30mm (Tubeless Ready) Alloy Double Wall 25mm SI 30 Mm Alloy 9x135mm QR Alloy 9x135mm QR Alloy 9x135mm SI 30 Mm Alloy 9x135mm SI 30 Mm <td>90°</td>	90°
WHEELSET TYRES CONTINENTAL Mountain king 29"x2,4" VITTORIA Terreno Dry 29"x1,75" VITTORIA T	ERGON GA30
TYRES CONTINENTAL Mountain king 27,5"x2,6" (Tubeless Ready) MAXXIS Rekon S - 27,5"x2,6" / M - L/XL-29"x2,4" VITTORIA Terreno Dry 29"x1,75" CONTINENTAL Mountain king 27,5"x2,6" (Tubeless Ready) MAXXIS Rekon S - 27,5"x2,6" / M - L/XL-29"x2,4" VITTORIA Terreno Dry 29"x1,75" CONTINENTAL Mountain king 27,5"x2,6" / M - L/XL-29"x2,4" VITTORIA Terreno Dry 29"x1,75"x2,6" / M - L/XL-29 CONTINENTAL Mountain king 27,5"x2,6" / M - L/XL-29 VITTORIA Terreno Dry 29"x1,75"x2,6" / M - L/XL-29 CONTINENTAL Mountain king 27,5"x2,6" / M - L/XL-29 VITTORIA Terreno Dry 29"x1,75"x2,6" / M - L/XL-29 CONTINENTAL Mountain king 27,5"x2,6" / M - L/XL-29 VITTORIA Terreno Dry 29"x1,75"x2,6" / M - L/XL-29 CONTINENTAL Mountain king 27,5"x2,6" / M - L/XL-29 VITTORIA Terreno Dry 29"x1,75"x2,6" / M - L/XL-29 CONTINENTAL REVEAL AND LIVE AND L	
YRES 27,5"x2,6" (Tubeless Ready) 29"x2,4" VITTORIA Terreno Dry 29"X1,75" 2! WHEEL SIZE 27,5" 27,5" (S) / 29" (M-L/XL) 29" 2! RIMS Alloy Double Wall 30mm (Tubeless Ready) Alloy Double Wall 30mm (Tubeless Ready) Alloy Double Wall 25mm Black Stainless Steel Black Stainless St	
WHEEL SIZE 27,5" 27,5" (S) / 29" (M-L/XL) 29" 29" RIMS Alloy Double Wall 30mm (Tubeless Ready) Alloy Double Wall 30mm (Tubeless Ready) Alloy Double Wall 30mm (Tubeless Ready) Alloy Double Wall 25mm Alloy D	CONTINENTAL Double Fighter III
Alloy Double Wall 30mm (Tubeless Ready) SPOKES Black Stainless Steel Black Stainless Steel Black Stainless Steel SHIMANO HB-MT400-B Boost 110 Thru-axle 15mm REAR HUB Alloy Double Wall 25mm Alloy Doub	29"x2,0"
Ready) Ready) Ready) Ready) SPOKES Black Stainless Steel Black Stainless Steel Black Stainless Steel Stainless Steel Black Stainless Steel	29"
SPOKES Black Stainless Steel Black Stainless Steel Stainless Steel Bl FRONT HUB SHIMANO HB-MT400-B Boost 110 Thru-axle 15mm SHIMANO HB-MT400-B Boost 110 Thru-axle 15mm Alloy 9x135mm QR SI REAR HUB SHIMANO Deore M6000 135mm SHIMANO HB-MT400-B Boost 148 Thru-axle 12mm BAFANG H400B 135mm SI DRIVETRAIN & BRAKES	Alloy Double Wall 25mm
FRONT HUB SHIMANO HB-MT400-B Boost 110 Thru-axle 15mm SHIMANO HB-MT400-B Boost 110 Thru-axle 15mm Alloy 9x135mm QR SI REAR HUB SHIMANO Deore M6000 135mm SHIMANO HB-MT400-B Boost 148 Thru-axle 12mm BAFANG H400B 135mm SI DRIVETRAIN & BRAKES	Dia di Chairdean Charl
Thru-axle 15mm Thru-axle 15mm Thru-axle 15mm Thru-axle 15mm 15 REAR HUB SHIMANO Deore M6000 135mm SHIMANO HB-MT400-B Boost 148 Thru-axle 12mm SI DRIVETRAIN & BRAKES	Black Stainless Steel
REAR HUB SHIMANO Deore M6000 135mm SHIMANO HB-MT400-B Boost 148 BAFANG H400B 135mm SI DRIVETRAIN & BRAKES	SHIMANO HB-MT400 100 Thru-axle 15mm
DRIVETRAIN & BRAKES SHIMANU Deore M6000 135mm Thru-axle 12mm BAFANG H400B 135mm SI	15111111
DRIVETRAIN & BRAKES	SHIMANO Deore M6000 135mm
BRAKES SHIMANO Hydraulic MT400 SHIMANO Hydraulic MT400 TEKTRO Cable Activated Hydraulic SI	SHIMANO Hydraulic MT200
HD-C705	STIMANO TIYOTAGIIC MT200
BRAKE ROTOR - Front SHIMANO SM-RT30 203mm SHIMANO SM-RT26 180mm SI	SHIMANO SM-RT10 180mm
BRAKE ROTOR - Rear SHIMANO SM-RT30 180mm SHIMANO SM-RT30 180mm SHIMANO SM-RT26 180mm SI	SHIMANO SM-RT10 180mm
REAR DERRAILEUR SHIMANO Deore 11S SRAM NX 11S MICROSHIFT AdventX 10S SI	SHIMANO Deore 10S
CASSETTE SHIMANO Deore 11S 11-51T SRAM Power Glid 1130 11-42 MICROSHIFT AdventX 10S 11-48T SI	SHIMANO Deore 10S 11-42T
SHIFTERS SHIMANO Deore 11S SRAM NX 11S MICROSHIFT AdventX 10S SI	SHIMANO Deore 10S
CHAINRING MIRANDA ChainFlow 3D BCD104 38T MIRANDA ChainFlow BCD104 38T SA	SAMOX BCD 104 36T
	SAMOX Shape 175/0
	SHIMANO CN-E6090
	Yes - FSA
	19/1
SAFETY & ACESSORIES	
•	ATRANVELO Tour AVS (max.: 25Kg)
FRONT LIGHT SPANNINGA Axendo 40 with reflector AX	AXA Blueline 30 with reflector
REAR LIGHT PICCADILY with reflector PI	PICCADILLY with reflector
KICKSTAND ATRANVELO Dux AT	ATRANVELO Dux
MUDGUARD SKS SI	SKS
	Yes
	Not included. Sold separately.
	SELLE ROYAL Essenza Moderate Gel
FSΔ Gossamer 31 6mm / 350mm	
SEAT POST AL Black 350mm 31,6mm/15mm /20mm AL Black 300mm 31,6mm /15mm Al	
,201111	AL Black 350mm 31,6mm/15mm
SEAT CLAMP Allow black with quick release Allow black with scrow Allow black with scrow Allow black with scrow Allow black with scrow	AL Black 350mm 31,6mm/15mm
	AL Black 350mm 31,6mm/15mm Alloy black with quick release
PEDALS UNION SP-827 Flat with reflectors UNION SP-400 Flat with reflectors UNION SP-400 Flat with reflectors U	AL Black 350mm 31,6mm/15mm