







- m) M (50cm)
, , ,
, , ,
, ,
, ,
Approx. 27 Kg
120Kg
cratch resistant with Glossy Powder Painting Scratch Resistant with Matte
Black Suit with Matte Finish
Step Aluminium High Step
Sr SUNTOUR Mobie E25 Air 75mm
-
-1/8" FSA 1.5" to 1-1/8" Tapered SHIS
-1/8" FSA 1.5" to 1-1/8" Tapered SHIS
ear Wheel 45Nm BROSE DRIVE S ALU 90Nm
grated on Downtube - Non 504Wh 36V - Semi-integrated on Downtube -
Removable
40km to 100km
Yes
charge time 4A - 3 to 6 hours total charge time
BROSE Allround
1210 / 51 250 / 1210 / 61inh f)
mm / 31.8mm / Flare 25° AL 660mm / 31.8mm (Straight)
mm - 7° AL 90mm - 31.8mm - adjustable 0-90°
ape ERGON GA30
Dry 29"x1,75" CONTINENTAL Double Fighter III 29"x2,0"
29"
25mm Alloy Double Wall 25mm
Black Stainless Steel
R SHIMANO HB-MT400 100 Thru Axle 15mm
S5mm SHIMANO Deore M6000 135mm
STIIMANO DEGLE MODOO 13311111
ivated Hydraulic HD-C705 SHIMANO Hydraulic MT200
6 180mm SHIMANO SM-RT10 180mm
6 180mm SHIMANO SM-RT10 180mm
ntX 10S SHIMANO Deore 10S
ntX 10S 11-48T SHIMANO Deore 10S 11-42T
ntX 10S SHIMANO Deore 10S
ow BCD104 38T SAMOX BCD 104 36T
SAM0X Shape 175/0
Dike series SHIMANO CN-E6090 10S E-Bike
51111/A/10 CIV 20000 100 E BINC
- Yes - FSA
IES - I JA
ATRANVELO Tour AVS (max.: 25Kg)
AXA Blueline 30 with reflector
AXA Slim with reflector
ATRANVELO Dux
SKS
Yes
separately. Not included. Sold separately.
el X Superflow SELLE ROYAL Essenza Moderate Gel
31,6mm /15mm
rew Alloy black with quick release
at with reflectors Alloy black with quick release UNION SP-827 Flat with reflectors
separately. Not included. Sold separately.

^{*} We reserve the right to modify product information that appears on this website without prior notice, including equipment, specifications, models, colors and materials.