









<b>a</b> ,	Olive with matte finish   Emerald Green with glossy varnish Low Step Aluminium Sr Suntour Raindon 34 Air Travel 120mm Axle Boost 110mm 27,5'' - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S MAG Horizontal 90Nm	S (42cm) - M (46cm) - L (50cm) Approx. 26kg 120kg Powder Painting Scratch Resistant with Matte or Glossy Varnish Black Fog with Matte Finish   Moon Grey Gloss with Glossy finish   Moon Grey Gloss with Glossy finish MTB Hardtail Aluminium Sr Suntour Raidon 34 Air Travel 130mm Boost 110mm 27,5" - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround Yes 5SA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6°	S/M (46cm) - L/XL (54cm) 26,5kg 145kg - White Star with glossy finish   Black Suit with matte finish   Desert Sand with matte finish   Desert Sand with matte finish   Desert Sand White Star with glossy finish   Black Suit with matte finish   Desert Sand with matte finish   Desert Sand White Star with glossy finish   Black Suit with matte finish   Desert Sand White Star with glossy finish   Black Suit with matte finish   Desert Sand White Star with glossy finish   Black Sr Suntour Mobie E25 Air 75mm - ACROS AZX-581 1.5" SHIS With Blocklock 150° Integrated Cables SHIMANO Steps E6100 60Nm 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time SHIMANO SC-E6100 AL 680mm / 31.8mm (Straight) AL 90mm - adjustable 0-90° - with integrated cables
x. 28kg er Painting Scratch Resistant fatte or Glossy Varnish Star with glossy Varnish   Happy ith matte finish   Black Suit with efinish nium Low Step Alloy 28" 5" to 1-1/8" Tapered SHIS E DRIVE C ALU 50Nm h 36V - Integrated on Downtube ovable to 100km hours total charge time E Allround Domm / 31.8mm (Curved) mm - 31.8mm - adjustable 0- N GP1 INENTAL Contact Cruiser	Approx. 28kg 190Kg Powder Painting Scratch Resistant with Matte or Glossy Varnish Hock Grey with matte finish   Dark Olive with matte finish   Dark Olive with matte finish   Dark Olive with matte finish   Emerald Green with glossy varnish Low Step Aluminium Sr Suntour Raindon 34 Air Travel 120mm Axle Boost 110mm 27,5" - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S MAG Horizontal 90Nm 522Wh 36V - Down Tube Integration - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 780mm / 31.8mm / Rise 20mm / 31.8mm (Straight) AL 50mm - 31.8mm - 0°	Approx. 26kg 120kg Powder Painting Scratch Resistant with Matte or Glossy Varnish Black Fog with Matte Finish   Moon Grey Gloss with Glossy finish MTB Hardtail Aluminium Sr Suntour Raidon 34 Air Travel 130mm Boost 110mm 27,5" - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight)	26,5kg 145kg - White Star with glossy finish   Black Suit with matte finish   Desert Sand with matte finish   Desert Sand Aluminium Low Step Sr Suntour Mobie E25 Air 75mm - ACROS AZX-581 1.5" SHIS With Blocklock 150° Integrated Cables SHIMANO Steps E6100 60Nm 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time SHIMANO SC-E6100 AL 680mm / 31.8mm (Straight) AL 90mm - adjustable 0-90° - with integrated cables
er Painting Scratch Resistant fatte or Glossy Varnish Star with glossy varnish   Happy vith matte finish   Black Suit with finish nium Low Step Alloy 28" 5" to 1-1/8" Tapered SHIS E DRIVE C ALU 50Nm h 36V - Integrated on Downtube ovable to 100km hours total charge time E Allround Omm / 31.8mm (Curved) mm - 31.8mm - adjustable 0- N GP1	190Kg Powder Painting Scratch Resistant with Matte or Glossy Varnish Hock Grey with matte finish   Dark Olive with matte finish   Emerald Green with glossy varnish Low Step Aluminium Sr Suntour Raindon 34 Air Travel 120mm Axle Boost 110mm 27,5" - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S MAG Horizontal 90Nm 522Wh 36V - Down Tube Integration - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 780mm / 31.8mm / Rise 20mm (Straight) FSA V-Drive 740mm / 31.8mm (Straight)	Approx. 26kg 120kg Powder Painting Scratch Resistant with Matte or Glossy Varnish Black Fog with Matte Finish   Moon Grey Gloss with Glossy finish MTB Hardtail Aluminium Sr Suntour Raidon 34 Air Travel 130mm Boost 110mm 27,5" - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight)	26,5kg 145kg - White Star with glossy finish   Black Suit with matte finish   Desert Sand with matte finish   Desert Sand Aluminium Low Step Sr Suntour Mobie E25 Air 75mm - ACROS AZX-581 1.5" SHIS With Blocklock 150° Integrated Cables SHIMANO Steps E6100 60Nm 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time SHIMANO SC-E6100 AL 680mm / 31.8mm (Straight) AL 90mm - adjustable 0-90° - with integrated cables
er Painting Scratch Resistant fatte or Glossy Varnish Star with glossy varnish   Happy vith matte finish   Black Suit with finish nium Low Step Alloy 28" 5" to 1-1/8" Tapered SHIS E DRIVE C ALU 50Nm h 36V - Integrated on Downtube ovable to 100km hours total charge time E Allround Omm / 31.8mm (Curved) mm - 31.8mm - adjustable 0- N GP1	190Kg Powder Painting Scratch Resistant with Matte or Glossy Varnish Hock Grey with matte finish   Dark Olive with matte finish   Emerald Green with glossy varnish Low Step Aluminium Sr Suntour Raindon 34 Air Travel 120mm Axle Boost 110mm 27,5" - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S MAG Horizontal 90Nm 522Wh 36V - Down Tube Integration - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 780mm / 31.8mm / Rise 20mm (Straight) FSA V-Drive 740mm / 31.8mm (Straight)	120kg Powder Painting Scratch Resistant with Matte or Glossy Varnish Black Fog with Matte Finish   Moon Grey Gloss with Glossy finish MTB Hardtail Aluminium Sr Suntour Raidon 34 Air Travel 130mm Boost 110mm 27,5" - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight)	145kg - White Star with glossy finish   Black Suit with matte finish   Desert Sand with matte finish   Desert Sand with matte finish   Desert Sand With matte finish   Desert Sand Aluminium Low Step Sr Suntour Mobie E25 Air 75mm - ACROS AZX-581 1.5" SHIS With Blocklock 150° Integrated Cables SHIMANO Steps E6100 60Nm 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time SHIMANO SC-E6100 AL 680mm / 31.8mm (Straight) AL 90mm - adjustable 0-90° - with integrated cables
fatte or Gossy Varnish Star with glossy varnish   Happy vith matte finish   Black Suit with finish nium Low Step Alloy 28" 5" to 1-1/8" Tapered SHIS E DRIVE C ALU 50Nm h 36V - Integrated on Downtube ovable to 100km hours total charge time E Allround Omm / 31.8mm (Curved) mm - 31.8mm - adjustable 0- N GP1 INENTAL Contact Cruiser	with Matte or Glossy Varnish Hock Grey with matte finish   Dark Olive with matte finish   Emerald Green with glossy varnish Low Step Aluminium Sr Suntour Raindon 34 Air Travel 120mm Axle Boost 110mm 27,5" - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S MAG Horizontal 90Nm 522Wh 36V - Down Tube Integration - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 780mm / 31.8mm / Rise 20mm (Straight) FSA V-Drive 740mm / 31.8mm (Straight)	with Matte or Glossy Varnish Black Fog with Matte Finish   Moon Grey Gloss with Glossy finish MTB Hardtail Aluminium Sr Suntour Raidon 34 Air Travel 130mm Boost 110mm 27,5" - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight)	Suit with matte finish   Desert Sand with matte finish Aluminium Low Step Sr Suntour Mobie E25 Air 75mm - ACROS AZX-581 1.5" SHIS With Blocklock 150° Integrated Cables SHIMANO Steps E6100 60Nm 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time SHIMANO SC-E6100 AL 680mm / 31.8mm (Straight) AL 90mm - adjustable 0-90° - with integrated cables
Star with glossy varnish   Happy vith matte finish   Black Suit with finish nium Low Step Alloy 28" 5" to 1-1/8" Tapered SHIS 5" to 1-1/8" Tapered SHIS 5 DRIVE C ALU 50Nm h 36V - Integrated on Downtube ovable to 100km hours total charge time 5 Allround 0mm / 31.8mm (Curved) mm - 31.8mm - adjustable 0- N GP1 INENTAL Contact Cruiser	Hock Grey with matte finish   Dark Olive with matte finish   Emerald Green with glossy varnish Low Step Aluminium Sr Suntour Raindon 34 Air Travel 120mm Axle Boost 110mm 27,5" - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S MAG Horizontal 90Nm 522Wh 36V - Down Tube Integration - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround Karsight) FSA V-Drive 740mm / 318mm (Straight) AL 50mm - 31.8mm - 0°	Black Fog with Matte Finish   Moon Grey Gloss with Glossy finish MTB Hardtail Aluminium Sr Suntour Raidon 34 Air Travel 130mm Boost 110mm 27,5" - FSA 1.5" to 1-1/8" Tapered SHIS - BROSE DRIVE S ALU 90Nm Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight)	Suit with matte finish   Desert Sand with matte finish Aluminium Low Step Sr Suntour Mobie E25 Air 75mm - ACROS AZX-581 1.5" SHIS With Blocklock 150° Integrated Cables SHIMANO Steps E6100 60Nm 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time SHIMANO SC-E6100 AL 680mm / 31.8mm (Straight) AL 90mm - adjustable 0-90° - with integrated cables
nium Low Step Alloy 28" 5" to 1-1/8" Tapered SHIS E DRIVE C ALU 50Nm h 36V - Integrated on Downtube ovable to 100km hours total charge time E Allround Omm / 31.8mm (Curved) mm - 31.8mm - adjustable 0- N GP1 INENTAL Contact Cruiser	Low Step Aluminium Sr Suntour Raindon 34 Air Travel 120mm Axle Boost 110mm 27,5'' - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S MAG Horizontal 90Nm 522Wh 36V - Down Tube Integration - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 780mm / 31.8mm / Rise 20mm (Straight) FSA V-Drive 740mm / 31.8mm (Straight) AL 50mm - 31.8mm - 0°	Sr Suntour Raidon 34 Air Travel 130mm Boost 110mm 27,5" - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight)	Aluminium Low Step Sr Suntour Mobie E25 Air 75mm - ACROS AZX-581 1.5" SHIS With Blocklock 150° Integrated Cables SHIMANO Steps E6100 60Nm 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time SHIMANO SC-E6100 AL 680mm / 31.8mm (Straight) AL 90mm - adjustable 0-90° - with integrated cables
Alloy 28" 5" to 1-1/8" Tapered SHIS E DRIVE C ALU 50Nm h 36V - Integrated on Downtube ovable to 100km hours total charge time E Allround 0mm / 31.8mm (Curved) mm - 31.8mm - adjustable 0- N GP1 INENTAL Contact Cruiser	Sr Suntour Raindon 34 Air Travel 120mm Axle Boost 110mm 27,5'' - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S MAG Horizontal 90Nm 522Wh 36V - Down Tube Integration - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 780mm / 31.8mm / Rise 20mm (Straight) FSA V-Drive 740mm / 31.8mm (Straight)	Sr Suntour Raidon 34 Air Travel 130mm Boost 110mm 27,5" - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight)	Sr Suntour Mobie E25 Air 75mm - ACROS AZX-581 1.5" SHIS With Blocklock 150° Integrated Cables SHIMANO Steps E6100 60Nm 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time SHIMANO SC-E6100 AL 680mm / 31.8mm (Straight) AL 90mm - adjustable 0-90° - with integrated cables
Alloy 28" 5" to 1-1/8" Tapered SHIS E DRIVE C ALU 50Nm h 36V - Integrated on Downtube ovable to 100km hours total charge time E Allround 0mm / 31.8mm (Curved) mm - 31.8mm - adjustable 0- N GP1 INENTAL Contact Cruiser	Sr Suntour Raindon 34 Air Travel 120mm Axle Boost 110mm 27,5'' - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S MAG Horizontal 90Nm 522Wh 36V - Down Tube Integration - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 780mm / 31.8mm / Rise 20mm (Straight) FSA V-Drive 740mm / 31.8mm (Straight)	Sr Suntour Raidon 34 Air Travel 130mm Boost 110mm 27,5" - FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight)	Sr Suntour Mobie E25 Air 75mm - ACROS AZX-581 1.5" SHIS With Blocklock 150° Integrated Cables SHIMANO Steps E6100 60Nm 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time SHIMANO SC-E6100 AL 680mm / 31.8mm (Straight) AL 90mm - adjustable 0-90° - with integrated cables
5" to 1-1/8" Tapered SHIS E DRIVE C ALU 50Nm h 36V - Integrated on Downtube ovable to 100km hours total charge time E Allround Dmm / 31.8mm (Curved) mm - 31.8mm - adjustable 0- N GP1 INENTAL Contact Cruiser	- SA 1.5" to 1-1/8" Tapered SHIS FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S MAG Horizontal 90Nm 522Wh 36V - Down Tube Integration - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 780mm / 31.8mm / Rise 20mm (Straight) FSA V-Drive 740mm / 31.8mm (Straight) AL 50mm - 31.8mm - 0°	- FSA 1.5" to 1-1/8" Tapered SHIS FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight)	Blocklock 150° Integrated Cables SHIMANO Steps E6100 60Nm 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time SHIMANO SC-E6100 AL 680mm / 31.8mm (Straight) AL 90mm - adjustable 0-90° - with integrated cables
E DRIVE C ALU 50Nm h 36V - Integrated on Downtube ovable to 100km hours total charge time E Allround 0mm / 31.8mm (Curved) mm - 31.8mm - adjustable 0- N GP1	BROSE DRIVE S MAG Horizontal 90Nm 522Wh 36V - Down Tube Integration - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 780mm / 31.8mm / Rise 20mm (Straight) FSA V-Drive 740mm / 31.8mm (Straight) AL 50mm - 31.8mm - 0°	BROSE DRIVE S ALU 90Nm Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6°	Blocklock 150° Integrated Cables SHIMANO Steps E6100 60Nm 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time SHIMANO SC-E6100 AL 680mm / 31.8mm (Straight) AL 90mm - adjustable 0-90° - with integrated cables
h 36V - Integrated on Downtube ovable to 100km hours total charge time Allround 0mm / 31.8mm (Curved) mm - 31.8mm - adjustable 0- N GP1 INENTAL Contact Cruiser	522Wh 36V - Down Tube Integration - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 780mm / 31.8mm / Rise 20mm (Straight) FSA V-Drive 740mm / 31.8mm (Straight) AL 50mm - 31.8mm - 0°	Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6°	SHIMANO Steps E6100 60Nm 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time SHIMANO SC-E6100 AL 680mm / 31.8mm (Straight) AL 90mm - adjustable 0-90° - with integrated cables
h 36V - Integrated on Downtube ovable to 100km hours total charge time Allround 0mm / 31.8mm (Curved) mm - 31.8mm - adjustable 0- N GP1 INENTAL Contact Cruiser	522Wh 36V - Down Tube Integration - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 780mm / 31.8mm / Rise 20mm (Straight) FSA V-Drive 740mm / 31.8mm (Straight) AL 50mm - 31.8mm - 0°	Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6°	504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time SHIMANO SC-E6100 AL 680mm / 31.8mm (Straight) AL 90mm - adjustable 0-90° - with integrated cables
h 36V - Integrated on Downtube ovable to 100km hours total charge time Allround 0mm / 31.8mm (Curved) mm - 31.8mm - adjustable 0- N GP1 INENTAL Contact Cruiser	522Wh 36V - Down Tube Integration - Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 780mm / 31.8mm / Rise 20mm (Straight) FSA V-Drive 740mm / 31.8mm (Straight) AL 50mm - 31.8mm - 0°	Snake Battery - 504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6°	504Wh 36V - Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time SHIMANO SC-E6100 AL 680mm / 31.8mm (Straight) AL 90mm - adjustable 0-90° - with integrated cables
ovable to 100km hours total charge time E Allround 0mm / 31.8mm (Curved) mm - 31.8mm - adjustable 0- N GP1 INENTAL Contact Cruiser	Removable 40km to 100km Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 780mm / 31.8mm / Rise 20mm (Straight) FSA V-Drive 740mm / 31.8mm (Straight) AL 50mm - 31.8mm - 0°	Integrated on Downtube - Removable 40km to 100km Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6°	- Removable 40km to 100km Yes 2A - 7 hours total charge time SHIMANO SC-E6100 AL 680mm / 31.8mm (Straight) AL 90mm - adjustable 0-90° - with integrated cables
hours total charge time E Allround Omm / 31.8mm (Curved) mm - 31.8mm - adjustable 0- N GP1 INENTAL Contact Cruiser	Yes 4A - 3 to 6 hours total charge time BROSE Allround AL 780mm / 31.8mm / Rise 20mm (Straight) FSA V-Drive 740mm / 318mm (Straight) AL 50mm - 31.8mm - 0°	Yes 2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6°	Yes 2A - 7 hours total charge time SHIMANO SC-E6100 AL 680mm / 31.8mm (Straight) AL 90mm - adjustable 0-90° - with integrated cables
Allround Omm / 31.8mm (Curved) mm - 31.8mm - adjustable 0- N GP1 INENTAL Contact Cruiser	4A - 3 to 6 hours total charge time BROSE Allround AL 780mm / 31.8mm / Rise 20mm (Straight) FSA V-Drive 740mm / 31.8mm (Straight) AL 50mm - 31.8mm - 0°	2A - 7 hours total charge time BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6°	2A - 7 hours total charge time SHIMANO SC-E6100 AL 680mm / 31.8mm (Straight) AL 90mm - adjustable 0-90° - with integrated cables
Allround Omm / 31.8mm (Curved) mm - 31.8mm - adjustable 0- N GP1 INENTAL Contact Cruiser	BROSE Allround AL 780mm / 31.8mm / Rise 20mm (Straight) FSA V-Drive 740mm / 31.8mm (Straight) AL 50mm - 31.8mm - 0°	BROSE Allround FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6°	SHIMANO SC-E6100 AL 680mm / 31.8mm (Straight) AL 90mm - adjustable 0-90° - with integrated cables
0mm / 31.8mm (Curved) mm - 31.8mm - adjustable 0- N GP1 INENTAL Contact Cruiser	AL 780mm / 31.8mm / Rise 20mm (Straight) FSA V-Drive 740mm / 31.8mm (Straight) AL 50mm - 31.8mm - 0°	FSA V-Drive 740mm / 31.8mm (Straight) FSA V-Drive 60mm/ 31.8mm / ±6°	AL 680mm / 31.8mm (Straight) AL 90mm - adjustable 0-90° - with integrated cables
mm - 31.8mm - adjustable 0- N GP1 INENTAL Contact Cruiser	(Straight) FSA V-Drive 740mm / 318mm (Straight) AL 50mm - 31.8mm - 0°	(Straight) FSA V-Drive 60mm/ 31.8mm / ±6°	AL 90mm - adjustable 0-90° - with integrated cables
mm - 31.8mm - adjustable 0- N GP1 INENTAL Contact Cruiser	(Straight) FSA V-Drive 740mm / 318mm (Straight) AL 50mm - 31.8mm - 0°	(Straight) FSA V-Drive 60mm/ 31.8mm / ±6°	AL 90mm - adjustable 0-90° - with integrated cables
N GP1 INENTAL Contact Cruiser		· · · ·	integrated cables
INENTAL Contact Cruiser	ERGON GA30	ERGON GA30	-
			ERGON GA30
	CONTINENTAL Mountain king	CONTINENTAL Mountain King	
	27,5"x2,6" (Tubeless Ready)	27,5"x2,6"	CONTINENTAL RaceKing 29''x 2,2''
	27,5"	27,5"	29''
Double Wall 25mm	Alloy Double Wall 30mm (Tubeless Ready)	Alloy Double Wall 25mm	Alloy Double Wall 25mm
Stainless Steel	Black Stainless Steel	Black Stainless Steel	Black Stainless Steel
ANO HB-MT400 100 Thru-axle ו	SHIMANO HB-MT400-B Boost 110 Thru-axle 15mm	SHIMANO HB-MT400-B Boost 110 Thru-axle 15mm	SHIMANO HB-MT400 100 Thru-axle 15mm
ANO Nexus SG-C6001-8D	SHIMANO Deore M6000 135mm	SHIMANO HB-MT400-B Boost 148 Thru-axle 12mm	SHIMANO Deore M6000 135mm
ANO Undraulia MT200	CHIMANO Hudroulio MT/00		
,	,	1	SHIMANO Hydraulic MT200 SHIMANO SM-RT10 180mm
			SHIMANO SM-RT10 180mm SHIMANO Deore M5100
			SHIMANO Deore CS-M5100-11 11-51T
ANO Nexus 8			SHIMANO Deore 11S
			SHIMANO SM-CRE61 38T
			SHIMANO FC-E6100 175mm
			Chain: KMC E11 Turbo e-bike series
1EBIE	Yes - FSA	Yes - FSA	Yes - SHIMANO
			ATRANVELO Tour AVS (max.: 25Kg)
			SPANNINGA Axendo 40 with reflector
			PICCADILLY with reflector
			ATRANVELO Dux
TYLLU DUA			SKS
			- C/IC
cluded. Sold senarately			- Not included. Sold separately.
	SELLE ROYAL Essenza Moderate Gel	SELLE ROYAL Shadow	SELLE ROYAL Essenza Moderate Black
		FSA Gossamer 350mm 31.6mm	Gel AL Black 350mm 31.6mm/15mm
	Al Black 350mm 316mm/15mm		5.666561111 51,01111/ 1011111
ck 350mm 31,6mm/15mm	AL Black 350mm 31,6mm/15mm	/20mm	Allow Islands and the state of the state
	AL Black 350mm 31,6mm/15mm Alloy black with quick release UNION SP-827 Flat with reflectors	/20mm Alloy black with quick release Union SP-21600 Flat with reflectors	Alloy black with quick release UNION SP 827 Flat with reflectors
	NO Hydraulic MT200 NO SM-RT10 180mm NO SM-RT10 180mm NO Nexus 8 IDA BCD 104 38T X Shape 175/0 NO CN-NX10 IEBIE IVELO Tour AVS (max: 25Kg) ueline 30 with reflector DILLY with reflector IVELO Dux cluded. Sold separately. ROYAL Rio Gel	NNO SM-RT10 180mm       SHIMANO SM-RT30 203mm         NNO SM-RT10 180mm       SHIMANO SM-RT30 180mm         SHIMANO Deore 11S       SHIMANO Deore 11S         INO Nexus 8       SHIMANO Deore 11S         IDA BCD 104 38T       MIRANDA ChainFlow 3D BCD104 38T         XShape 175/0       SAMOX Shape 170/0         INO CN-NX10       KMC E11 Turbo e-bike series         IEBIE       Yes - FSA         IVELO Tour AVS (max.: 25Kg)       ATRANVELO Tour AVS (max.: 25Kg)         ueline 30 with reflector       SPANNINGA Axendo 40 with reflector         DILLY with reflector       PICCADILY with reflector         IVELO Dux       ATRANVELO Dux         SKS       Yes         cluded. Sold separately.       Not included. Sold separately.         ROYAL Rio Gel       SELLE ROYAL Essenza Moderate Gel	NNO SM-RT10 180mmSHIMANO SM-RT30 203mmSHIMANO SM-RT10 180mmNNO SM-RT10 180mmSHIMANO SM-RT30 180mmSHIMANO SM-RT10 180mmSNO SM-RT10 180mmSHIMANO Deore 11SSHIMANO Deore 10SSHIMANO Deore 11SSHIMANO Deore 10SSHIMANO Deore 10SNO Nexus 8SHIMANO Deore 11SSHIMANO Deore 10SIDA BCD 104 38TMIRANDA ChainFlow 3D BCD104 38TSAMOX BCD 104 36TX Shape 175/0SAMOX Shape 170/0SAMOX Shape 175/5INO CN-NX10KMC E11 Turbo e-bike seriesSHIMANO CN-E6090IEBIEYes - FSAYes - FSAIVELO Tour AVS (max: 25Kg)ATRANVELO Tour AVS (max: 25Kg)-IULY with reflectorSPANNINGA Axendo 40 with reflector-IVELO DuxATRANVELO Dux-SKSYesYesYesCluded. Sold separately.Not included. Sold separately.Not included. Sold separately.ROYAL Rio GelSELLE ROYAL Essenza Moderate GelSELLE ROYAL S50mm 31.6mm

\* We reserve the right to modify product information that appears on this website without prior notice, including equipment, specifications, models, colors and materials.