







PRODUCT INFORMATION			
NOTE	-	We reserve the right to modify the information of the products that appear on this website without prior notice, including equipment, specifications, models, colors and materials.	_
FRAME SIZES	S (45cm) - M (50cm) - L (55cm)	S/M (46cm) - L/XL (54cm)	M (50cm) - L (55cm)
WEIGHT	Approx. 28kg	Approx. 26,5kg	Approx. 28kg
MAXIMUM BIKE & RIDER WEIGHT	120kg	145kg	120kg
PAINTING	Powder Painting Scratch Resistant with Matte or Glossy Varnish	Powder Painting Scratch Resistant with Matte or Glossy Varnish	Powder Painting Scratch Resistant with Matte or Glossy Varnish
COLOUR(s)	White Star with glossy varnish   Happy Blue with matte finish   Black Suit with matte finish	White Star with glossy varnish   Happy Blue with matte finish   Black Suit with matte finish   Desert Sand with matte finish	Black Suit with matte finish
FRAME			
FRAME	Aluminium Low Step	Aluminium Low Step	Aluminium Low Step
FORK	Rigid Alloy 28"	Rigid Alloy 28"	Rigid Alloy 28"
HEADSET	FSA 1.5" to 1-1/8" Tapered SHIS	ACROS AZX-581 1.5" SHIS With Blocklock 150° Integrated Cables	FSA 1.5" to 1-1/8" Tapered SHIS
E-BIKE SYSTEM			
DRIVE UNIT	BROSE DRIVE C ALU 50Nm	SHIMANO Steps E6100 60Nm	BROSE DRIVE C Horizontal 50Nm
BATTERY	504Wh 36V - Integrated on Downtube - Removable	504Wh 36V - Integrated on Downtube - Removable	504Wh 36V - Semi-Integrated on Downtube - Removable
RANGE	40km to 100km	40km to 100km	40km to 100km
BATTERY LOCK KEY	Yes	Yes	Yes
CHARGER	2A - 7 hours total charge time	2A - 7 hours total charge time	4A - 4 to 5 hours total charge time
DISPLAY	BROSE Allround	SHIMANO SC-E6100	MARQUARDT Display
COCKPIT			· '
HANDLEBAR	AL 660mm / 31.8mm (Curved)	AL 660mm / 31.8mm (Curved)	AL 660mm / 31.8mm (Curved)
STEM	AL 90mm - 31.8mm - adjustable 0-90°	AL 90mm - adjustable 0-90° - with integrated cables	AL 90mm - 31.8mm - adjustable 0-90°
GRIPS	ERGON GP1	ERGON GP1	ERGOTECH EG-AMBITION
WHEELSET			
TYRES	CONTINENTAL Contact Cruiser 28"x2,2"	CONTINENTAL Contact Urban 28"x2,2"	CONTINENTAL Ride Cruiser 28"x2,2"
WHEEL SIZE	28"	28"	28"
RIMS	Alloy Double Wall 25mm	Alloy Double Wall 25mm	Alloy Double 25mm
SPOKES	Black Stainless Steel	Black Stainless Steel	Black Stainless Steel
FRONT HUB	SHIMANO HB-MT400 100 Thru-axle 15mm	SHIMANO HB-MT400 100 Thru-axle 15mm	SHIMANO HB-MT400 100 Thru-axle 15mm
REAR HUB	SHIMANO Nexus SG-C6001-8D	SHIMANO Nexus SG-C6001-8D	SHIMANO NEXUS SG-C6001 135mm
DRIVETRAIN & BRAKES			
BRAKES	SHIMANO Hydraulic MT200	SHIMANO Hydraulic MT200	CLARKS Hydraulic M2
BRAKE ROTOR - Front	SHIMANO SM-RT10 180mm	SHIMANO SM-RT10 180mm	CL HJ-DXR1814 180mm
BRAKE ROTOR - Rear	SHIMANO SM-RT10 180mm	SHIMANO SM-RT10 180mm	CL HJ-DXR1814 180mm
SHIFTERS	SHIMANO Nexus 8	SHIMANO Nexus 8	SHIMANO NEXUS 8
CHAINRING	MIRANDA BCD 104 38T	SHIMANO SM-CRE61 38T	MIRANDA ChainFlow BCD 104 38T
CRANK	SAMOX Shape 175/0	SHIMANO FC-E6100 175mm	SAMOX Shape 175
CHAIN	SHIMANO CN-NX10	SHIMANO CN-NX10	SHIMANO CN-NX10
CHAINGUARD	Yes - HEBIE	Yes - HEBIE	Yes - HEBIE
SAFETY & ACESSORIES			
RACK	ATRANVELO Tour AVS (max.: 25Kg)	ATRANVELO Tour AVS (max.: 25Kg)	ATRANVELO City AVS (max.: 25Kg)
FRONT LIGHT	AXA Blueline 30 with reflector	SPANNINGA Axendo 40 with reflector	AXA Blueline 30 with reflector
REAR LIGHT	PICCADILLY with reflector	PICCADILLY with reflector	PICCADILY with reflector
KICKSTAND	ATRANVELO Dux	ATRANVELO Dux	ATRANVELO Dux
MUDGUARD	SKS	SKS	SKS
BELL	Yes	Yes	Yes
BOTTLE CAGE	Not included. Sold separately.	Not included. Sold separately.	Not included. Sold separately.
SADDLE	SELLE ROYAL Rio Gel	SELLE ROYAL Rio Gel	SELLE ROYAL Rio Gel
SEAT POST	AL Black 350mm 31,6mm/15mm	AL Black 300mm 31,6mm/15mm	AL Black 350mm 27.2mm/15mm
SEAT CLAMP	Alloy black with quick release	Alloy black with quick release	Alloy black with quick release
PEDALS	UNION SP-827 Flat with reflectors	UNION SP-827 Flat with reflectors	UNION SP-827 with reflectors
FRAMELOCK	Not included. Sold separately.	AXA Block XXL	Not included. Sold separately.

<sup>\*</sup> We reserve the right to modify product information that appears on this website without prior notice, including equipment, specifications, models, colors and materials.