









S (46cm) - M (52cm) - L (56cm) Approx. 24kg 145kg Powder Painting Scratch Resistant With Matte Varnish Moon Grey with matte finish Desert Sand with matte finish Aluminium Low Step Rigid Alloy 28" SHIS 1-1/8" BAFANG H400B Rear Wheel 45Nm 360Wh 36V - Integrated on Downtube - Non Removable 40km to 100km -	M (50cm) - L (55cm) Approx. 28kg 120kg Powder Painting Scratch Resistant with Matte or Glossy Varnish Black Suit with matte finish Aluminium Low Step Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE C Horizontal 50Nm 504Wh 36V - Semi-Integrated on Downtube - Removable	- Approx. 24 Kg 150kg Powder Painting Scratch Resistant With Matte Varnish Moon Grey with matte finish Desert Sand with matte finish Aluminium High Step Rigid Alloy 28" SHIS 1-1/8" BAFANG H400B Rear Wheel 45Nm	M (44cm) - L (48cm) Approx. 25kg 120kg Powder Painting Scratch Resistant with Matte or Glossy Varnish White Star with glossy varnish Happy Blue with matte finish Black Suit with matte finish Aluminium Low Step Rigid Alloy 28" Acros 1.5" to 1-1/8" Tapered SHIS
145kg Powder Painting Scratch Resistant With Matte Varnish Moon Grey with matte finish Desert Sand with matte finish Aluminium Low Step Rigid Alloy 28" SHIS 1-1/8" BAFANG H400B Rear Wheel 45Nm 360Wh 36V - Integrated on Downtube - Non Removable	120kg Powder Painting Scratch Resistant with Matte or Glossy Varnish Black Suit with matte finish Aluminium Low Step Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE C Horizontal 50Nm 504Wh 36V - Semi-Integrated on	150kg Powder Painting Scratch Resistant With Matte Varnish Moon Grey with matte finish Desert Sand with matte finish Aluminium High Step Rigid Alloy 28" SHIS 1-1/8"	120kg Powder Painting Scratch Resistant with Matte or Glossy Varnish White Star with glossy varnish Happy Blue with matte finish Black Suit with matte finish Aluminium Low Step Rigid Alloy 28"
Powder Painting Scratch Resistant With Matte Varnish Moon Grey with matte finish Desert Sand with matte finish Aluminium Low Step Rigid Alloy 28" SHIS 1-1/8" BAFANG H400B Rear Wheel 45Nm 360Wh 36V - Integrated on Downtube - Non Removable	Powder Painting Scratch Resistant with Matte or Glossy Varnish Black Suit with matte finish Aluminium Low Step Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE C Horizontal 50Nm 504Wh 36V - Semi-Integrated on	Powder Painting Scratch Resistant With Matte Varnish Moon Grey with matte finish Desert Sand with matte finish Aluminium High Step Rigid Alloy 28" SHIS 1-1/8"	Powder Painting Scratch Resistant with Matte or Glossy Varnish White Star with glossy varnish Happy Blue with matte finish Black Suit with matte finish Aluminium Low Step Rigid Alloy 28"
With Matte Varnish Moon Grey with matte finish Desert Sand with matte finish Aluminium Low Step Rigid Alloy 28" SHIS 1-1/8" BAFANG H400B Rear Wheel 45Nm 360Wh 36V - Integrated on Downtube - Non Removable	with Matte or Glossy Varnish Black Suit with matte finish Aluminium Low Step Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE C Horizontal 50Nm 504Wh 36V - Semi-Integrated on	With Matte Varnish Moon Grey with matte finish Desert Sand with matte finish Aluminium High Step Rigid Alloy 28" SHIS 1-1/8"	with Matte or Glossy Varnish White Star with glossy varnish Happy Blue with matte finish Black Suit with matte finish Aluminium Low Step Rigid Alloy 28"
Sand with matte finish Aluminium Low Step Rigid Alloy 28" SHIS 1-1/8" BAFANG H400B Rear Wheel 45Nm 360Wh 36V - Integrated on Downtube - Non Removable	Aluminium Low Step Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE C Horizontal 50Nm 504Wh 36V - Semi-Integrated on	Aluminium High Step Rigid Alloy 28" SHIS 1-1/8"	Blue with matte finish Black Suit with matte finish Aluminium Low Step Rigid Alloy 28"
Rigid Alloy 28" SHIS 1-1/8" BAFANG H400B Rear Wheel 45Nm 360Wh 36V - Integrated on Downtube - Non Removable	Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE C Horizontal 50Nm 504Wh 36V - Semi-Integrated on	Rigid Alloy 28" SHIS 1-1/8"	Rigid Alloy 28"
Rigid Alloy 28" SHIS 1-1/8" BAFANG H400B Rear Wheel 45Nm 360Wh 36V - Integrated on Downtube - Non Removable	Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE C Horizontal 50Nm 504Wh 36V - Semi-Integrated on	Rigid Alloy 28" SHIS 1-1/8"	Rigid Alloy 28"
Rigid Alloy 28" SHIS 1-1/8" BAFANG H400B Rear Wheel 45Nm 360Wh 36V - Integrated on Downtube - Non Removable	Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE C Horizontal 50Nm 504Wh 36V - Semi-Integrated on	Rigid Alloy 28" SHIS 1-1/8"	Rigid Alloy 28"
SHIS 1-1/8" BAFANG H400B Rear Wheel 45Nm 360Wh 36V - Integrated on Downtube - Non Removable	FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE C Horizontal 50Nm 504Wh 36V - Semi-Integrated on	SHIS 1-1/8"	· ·
360Wh 36V - Integrated on Downtube - Non Removable	BROSE DRIVE C Horizontal 50Nm 504Wh 36V - Semi-Integrated on	BAFANG H400B Rear Wheel 45Nm	
360Wh 36V - Integrated on Downtube - Non Removable	504Wh 36V - Semi-Integrated on	BAFANG H400B Rear Wheel 45Nm	
360Wh 36V - Integrated on Downtube - Non Removable	504Wh 36V - Semi-Integrated on		SHIMANO STEPS E5000 40Nm
		360Wh 36V - Integrated on Downtube - Non Removable	
-	40km to 100km	40km to 100km	40km to 100km
	Yes	-	Yes
2A - 5 hours total charge time	4A - 4 to 5 hours total charge time	2A - 5 hours total charge time	2A - 6 hours total charge time
BAFANG DP.C11	MARQUARDT Display	BAFANG DP.C11	SHIMANO SC-E6100
	1 7		
AL 660mm / 31.8mm (Curved)	AL 660mm / 31.8mm (Curved)	AL 660mm / 31.8mm (Straight)	AL 660mm / 31.8mm (Curved)
· · · · · · · · · · · · · · · · · · ·			AL 90mm - 31.8mm - adjustable 0-
90°	90°	AL 100mm - 31.8mm - 7°	90°
HERRMANS DD36 Ergonomic	ERGOTECH EG-AMBITION	HERRMANS DD36 Ergonomic	HERRMANS DD36
CONTINENTAL Contact Cruiser 28"x2,0"	CONTINENTAL Ride Cruiser 28"x2,2"	CONTINENTAL Double Fighter III 29''x2,0''	CONTINENTAL Ride Cruiser 28"x2,0"
28"	28"	29''	28"
Alloy Double Wall 25mm	Alloy Double 25mm	Alloy Double Wall 25mm	Alloy Double Wall 25mm
Stainless Steel	Black Stainless Steel	Stainless Steel	Black Stainless Steel
SHIMANO HB-TX506 9x100mm QR	SHIMANO HB-MT400 100 Thru-axle 15mm	SHIMANO HB-TX506 9x100mm QR	SHIMANO HB-MT400 100 Thru-axle 15mm
BAFANG H400B 135mm	SHIMANO NEXUS SG-C6001 135mm	BAFANG H400B 135mm	SHIMANO FH-TX505 135mm
ALHONGA Hydraulic HJ-HT474	CLARKS Hydraulic M2	ALHONGA Hydraulic HJ-HT474	SHIMANO Hydraulic MT200
ALHONGA HJ-DXR1806 180MM	CL HJ-DXR1814 180mm	ALHONGA HJ-DXR1806 180MM	SHIMANO SM-RT 180mm
ALHONGA HJ-DXR1806 180MM	CL HJ-DXR1814 180mm	ALHONGA HJ-DXR1806 180MM	SHIMANO SM-RT 160mm
SHIMANO Altus 9S	-	SHIMANO Altus 9S	SHIMANO Altus 9S
SHIMANO Altus 9S 11-36T	-	SHIMANO Altus 9S 11-36T	SHIMANO Altus 9S 11-36T
SHIMANO Altus 9S	SHIMANO NEXUS 8	SHIMANO Altus 9S	SHIMANO Altus 9S
MIRANDA ChainFlow BCD104 38T	MIRANDA ChainFlow BCD 104 38T	MIRANDA ChainFlow BCD104 38T	SHIMANO SN-CRE50 38T
MIRANDA JIS 170	SAMOX Shape 175	MIRANDA JIS 170	SHIMAN0 FC-E5010 - 175
			SHIMANO CN-HG53
Yes - SKS	Yes - HEBIE	Yes - MIRANDA	Yes - SKS
ATRANVELO City AVS (max.: 25Kg)	ATRANVELO City AVS (max.: 25Kg)	ATRANVELO City AVS (max.: 25Kg)	ATRANVELO Tour AVS (max.: 25Kg)
AXA Ecoline 15 with reflector	AXA Blueline 30 with reflector	AXA Ecoline 15 with reflector	AXA Blueline 30 with reflector
AXA Slim with reflector	PICCADILY with reflector	AXA Slim with reflector	PICCADILLY with reflector
ATRANVELO Dux	ATRANVELO Dux	ATRANVELO Dux	ATRANVELO Dux
SKS		SKS	SKS
National of C. I.		- Notice deviled at 2011	Yes
. ,		. ,	Not included. Frame not prepared.
			SELLE ROYAL Rio Gel
· · · · · · · · · · · · · · · · · · ·			AL Black 350mm 30,9mm/15mm
,		,	Alloy black with quick release
			UNION SP-827 Flat with reflectors Not included. Sold separately.
	AL 90mm - 31.8mm - adjustable 0- 90° HERRMANS DD36 Ergonomic CONTINENTAL Contact Cruiser 28"x2,0" 28" Alloy Double Wall 25mm Stainless Steel SHIMANO HB-TX506 9x100mm QR BAFANG H400B 135mm ALHONGA Hydraulic HJ-HT474 ALHONGA HJ-DXR1806 180MM ALHONGA HJ-DXR1806 180MM SHIMANO Altus 9S SHIMANO Altus 9S SHIMANO Altus 9S MIRANDA ChainFlow BCD104 38T MIRANDA JIS 170 SHIMANO CN-HG53 Yes - SKS ATRANVELO City AVS (max.: 25Kg) AXA Ecoline 15 with reflector AXA Slim with reflector	AL 90mm - 31.8mm - adjustable 0- 90°	AL 90mm - 31.8mm - adjustable 0-90° AL 90mm - 31.8mm - adjustable 0-90° AL 100mm - 31.8mm - 70° 90° 90° 90° 90° 90° 90° 90° 90° 90° 9

^{*} We reserve the right to modify product information that appears on this website without prior notice, including equipment, specifications, models, colors and materials.