



B400 Urban Low Step
€ 1,399



M850 Wild Full Suspension
€ 2,699



C800 Trekking Suspension
€ 1,549

PRODUCT INFORMATION

FRAME SIZES	S (46cm) - M (52cm) - L (56cm)	S (38cm) - M (42cm) - L (46cm)	M (50cm)
WEIGHT	Approx. 24kg	Approx. 26kg	Approx. 27 Kg
MAXIMUM BIKE & RIDER WEIGHT	145kg	135kg	120Kg
PAINTING	Powder Painting Scratch Resistant With Matte Varnish	Powder painting scratch resistant with Glossy Varnish	Powder Painting Scratch Resistant with Matte
COLOUR(s)	Moon Grey with matte finish Desert Sand with matte finish	Dark Night with gloss finish Pure Red with gloss finish	Black Suit with Matte Finish

FRAME

FRAME	Aluminium Low Step	MTB FS Full Aluminium 150mm	Aluminium High Step
SUSPENSION	-	Rockshox 35S Air Travel 150mm Axle Boost 110mm 29"	Sr SUNTOUR Mobie E25 Air 75mm
FORK	Rigid Alloy 28"	-	-
HEADSET	SHIS 1-1/8"	ACROS AZX-581 1.5" SHIS With Blocklock 150° Integrated Cables	FSA 1.5" to 1-1/8" Tapered SHIS
REAR SHOCK	-	ROCKSHOX Deluxe Select+ Travel 150mm Trunnion (205x57,5)	-

E-BIKE SYSTEM

DRIVE UNIT	BAFANG H400B Rear Wheel 45Nm	SHIMANO Steps EP800 85Nm	BROSE DRIVE S ALU 90Nm
BATTERY	360Wh 36V - Integrated on Downtube - Non Removable	630Wh 36V - Integrated on Downtube - Removable	504Wh 36V - Semi-integrated on Downtube - Removable
RANGE	40km to 100km	40km to 100km	40km to 100km
BATTERY LOCK KEY	-	Yes	Yes
CHARGER	2A - 5 hours total charge time	2A - 6 to 8 hours total charge time	4A - 3 to 6 hours total charge time
DISPLAY	BAFANG DP.C11	SHIMANO SC-E7000	BROSE Allround

COCKPIT

HANDLEBAR	AL 660mm / 31.8mm (Curved)	AL 780mm / 31.8mm / Rise 20mm (Straight)	AL 660mm / 31.8mm (Straight)
STEM	AL 90mm - 31.8mm - adjustable 0-90°	AL 40mm - 31.8mm - 0°	AL 90mm - 31.8mm - adjustable 0-90°
GRIPS	HERRMANS DD36 Ergonomic	VP VPG 122A	ERGON GA30

WHEELSET

TYRES	CONTINENTAL Contact Cruiser 28"x2,0"	CONTINENTAL MountainKing 27,5"x2,6" / TrailKing 29"x2,4" (Rear Tyre Tubeless Ready)	CONTINENTAL Double Fighter III 29"x2,0"
WHEEL SIZE	28"	Mullet: 27,5" / 29"	29"
RIMS	Alloy Double Wall 25mm	Alloy Double Wall Front: 30mm/ Rear: 35mm (Tubeless Ready)	Alloy Double Wall 25mm
SPOKES	Stainless Steel	Black Stainless Steel	Black Stainless Steel
FRONT HUB	SHIMANO HB-TX506 9x100mm QR	Boost 110 Thru-axle 15mm	SHIMANO HB-MT400 100 Thru Axle 15mm
REAR HUB	BAFANG H400B 135mm	Boost 148 Thru-axle 12mm	SHIMANO Deore M6000 135mm

DRIVETRAIN & BRAKES

BRAKES	ALHONGA Hydraulic HJ-HT474	SHIMANO Hydraulic MT520	SHIMANO Hydraulic MT200
BRAKE ROTOR - Front	ALHONGA HJ-DXR1806 180MM	SHIMANO SM-RT30 203mm	SHIMANO SM-RT10 180mm
BRAKE ROTOR - Rear	ALHONGA HJ-DXR1806 180MM	SHIMANO SM-RT30 180mm	SHIMANO SM-RT10 180mm
REAR DERRAILEUR	SHIMANO Altus 9S	SHIMANO Deore 11S	SHIMANO Deore 10S
CASSETTE	SHIMANO Altus 9S 11-36T	SHIMANO Deore 11S 11-51T	SHIMANO Deore 10S 11-42T
SHIFTERS	SHIMANO Altus 9S	SHIMANO Deore 11S	SHIMANO Deore 10S
CHAINRING	MIRANDA ChainFlow BCD104 38T	MIRANDA ChainFlow 3D BCD104 36T	SAMOX BCD 104 36T
CRANK	MIRANDA JIS 170	SHIMANO FC-EM600 165	SAMOX Shape 175/0
CHAIN	SHIMANO CN-HG53	KMC e11 Turbo e-bike series	SHIMANO CN-E6090 10S E-Bike
CHAINGUARD	Yes - SKS	Yes - GW	Yes - FSA

SAFETY & ACESSORIES

RACK	ATRANVELO City AVS (max.: 25Kg)	-	ATRANVELO Tour AVS (max.: 25Kg)
FRONT LIGHT	AXA Ecoline 15 with reflector	LITEMOVE SE-110 with reflector 110 Lux	AXA Blueline 30 with reflector
REAR LIGHT	AXA Slim with reflector	-	AXA Slim with reflector
KICKSTAND	ATRANVELO Dux	-	ATRANVELO Dux
MUDGUARD	SKS	-	SKS
BELL	-	-	Yes
BOTTLE CAGE	Not included. Sold separately.	FIDLOCK Twist	Not included. Sold separately.
SADDLE	SELLE ROYAL Rio Gel	SELLE SAN MARCO GND	SELLE ROYAL Essenza Moderate Gel
SEAT POST	AL Black 300mm 31,6mm/15mm	KindShock Dropper Post Lev Integra Travel 150mm	AL Black 350mm 31,6mm/15mm
SEAT CLAMP	Alloy black with screw	Alloy black with screw	Alloy black with quick release
PEDALS	NECO with reflectors	MARWI SP-400 Flat with reflectors	UNION SP-827 Flat with reflectors
FRAMELOCK	Not included. Sold separately.	-	Not included. Sold separately.

* We reserve the right to modify product information that appears on this website without prior notice, including equipment, specifications, models, colors and materials.