







PRODUCT INFORMATION			
FRAME SIZES	M (50cm) - L (55cm)	M (50cm)	S-M (42cm) - L/XL (46cm)
WEIGHT	Approx. 28kg	Approx. 27 Kg	Approx. 26Kg
MAXIMUM BIKE & RIDER WEIGHT	120kg	120Kg	135Kg
NAME OF THE OWNER OWNER OF THE OWNER OWNE	Powder Painting Scratch Resistant with Matte o	r	Powder Painting Scratch Resistant with Matte
PAINTING	Glossy Varnish	Powder Painting Scratch Resistant with Matte	Varnish  Black Fog with matte finish   Pure Red with
COLOUR(s)	Black Suit with matte finish	Black Suit with Matte Finish	matte finish   Rock Blue with matte finish
FRAME			
RAME	Aluminium Low Step	Aluminium High Step	MTB Hardtail Aluminum
SUSPENSION	-	Sr SUNTOUR Mobie E25 Air 75mm	Rockshox 35S Air Travel 120mm Axle Boost 110mm 27.5''/29''
ORK	Rigid Alloy 28"	-	-
HEADSET	FSA 1.5" to 1-1/8" Tapered SHIS	FSA 1.5" to 1-1/8" Tapered SHIS	FSA 1.5" to 1-1/8" Tapered SHIS
E-BIKE SYSTEM			
PRIVE UNIT	BROSE DRIVE C Horizontal 50Nm	BROSE DRIVE S ALU 90Nm	BROSE DRIVE S MAG Horizontal 90Nm
BATTERY	504Wh 36V - Semi-Integrated on Downtube - Removable	504Wh 36V - Semi-integrated on Downtube - Removable	522Wh 36V - Integrated on Downtube - Removable
RANGE	40km to 100km	40km to 100km	40km to 100km
ATTERY LOCK KEY	Yes	Yes	Yes
HARGER	4A - 4 to 5 hours total charge time	4A - 3 to 6 hours total charge time	4A - 3 to 6 hours total charge time
DISPLAY	MARQUARDT Display	BROSE Allround	Brose Allround
	MARQUARD I DISPIAY	BRUSE AIII OUT IU	Brose Allrourid
COCKPIT			
IANDLEBAR	AL 660mm / 31.8mm (Curved)	AL 660mm / 31.8mm (Straight)	FSA V-Drive 740mm / 31.8mm (Straight)
STEM	AL 90mm - 31.8mm - adjustable 0-90°	AL 90mm - 31.8mm - adjustable 0-90°	FSA V-Drive 60mm/ 31.8mm / ±6°
RIPS	ERGOTECH EG-AMBITION	ERGON GA30	ERGON GA30
VHEELSET			
YRES	CONTINENTAL Ride Cruiser 28"x2,2"	CONTINENTAL Double Fighter III 29"x2,0"	MAXXIS Rekon S - 27,5"x2,6" / M - L/XL- 29"x2,4
VHEEL SIZE	28"	29"	27,5" (S) / 29" (M-L/XL)
RIMS	Alloy Double 25mm	Alloy Double Wall 25mm	Alloy Double Wall 30mm (Tubeless Ready)
POKES	Black Stainless Steel	Black Stainless Steel	Black Stainless Steel
RONT HUB	SHIMANO HB-MT400 100 Thru-axle 15mm	SHIMANO HB-MT400 100 Thru Axle 15mm	SHIMANO HB-MT400-B Boost 110 Thru-axle 15mm
REAR HUB	SHIMANO NEXUS SG-C6001 135mm	SHIMANO Deore M6000 135mm	SHIMANO HB-MT400-B Boost 148 Thru-axle 12mm
DRIVETRAIN & BRAKES			
BRAKES	CLARKS Hydraulic M2	SHIMANO Hydraulic MT200	SHIMANO Hydraulic MT400
BRAKE ROTOR - Front	CL HJ-DXR1814 180mm	SHIMANO SM-RT10 180mm	SHIMANO SM-RT30 203mm
BRAKE ROTOR - Rear	CL HJ-DXR1814 180mm	SHIMANO SM-RT10 180mm	SHIMANO SM-RT30 180mm
REAR DERRAILEUR		SHIMANO Deore 10S	SRAM NX 11S
ASSETTE	_	SHIMANO Deore 10S 11-42T	SRAM Power Glid 1130 11-42
HIFTERS	SHIMANO NEXUS 8	SHIMANO Deore 10S	SRAM NX 11S
CHAINRING	MIRANDA ChainFlow BCD 104 38T	SAMOX BCD 104 36T	MIRANDA ChainFlow 3D BCD104 38T
RANK	SAMOX Shape 175	SAMOX Shape 175/0	SAMOX Shape 170/0
CHAIN	SHIMANO CN-NX10	SHIMANO CN-E6090 10S E-Bike	KMC E11 Turbo e-bike series
CAFETY & ACECCODIES	Yes - HEBIE	Yes - FSA	Yes - FSA
SAFETY & ACESSORIES			
ACK	ATRANVELO City AVS (max.: 25Kg)	ATRANVELO Tour AVS (max.: 25Kg)	ATRANVELO Tour AVS (max.: 25Kg)
RONT LIGHT	AXA Blueline 30 with reflector	AXA Blueline 30 with reflector	SPANNINGA Axendo 40 with reflector
EAR LIGHT	PICCADILY with reflector	AXA Slim with reflector	PICCADILY with reflector
ICKSTAND	ATRANVELO Dux	ATRANVELO Dux	ATRANVELO Dux
IUDGUARD	SKS	SKS	SKS
ELL	Yes	Yes	Yes
OTTLE CAGE	Not included. Sold separately.	Not included. Sold separately.	Not included. Sold separately.
ADDLE	SELLE ROYAL Rio Gel	SELLE ROYAL Essenza Moderate Gel	SELLE SAN MARCO X3 e-bike black
EAT POST	AL Black 350mm 27.2mm/15mm	AL Black 350mm 31,6mm/15mm	FSA Gossamer 31.6mm / 350mm /20mm
EAT CLAMP	Alloy black with quick release	Alloy black with quick release	Alloy black with screw
			· ·
PEDALS	UNION SP-827 with reflectors	UNION SP-827 Flat with reflectors	UNION SP-400 Flat with reflectors

 $<sup>^{\</sup>star}$  We reserve the right to modify product information that appears on this website without prior notice, including equipment, specifications, models, colors and materials.