









serve the right to modify the nation of the products that ar on this website without prior including equipment, including equipment, ications, models, colors and rials. 46cm) - L/XL (54cm) x. 26,5kg Per Painting Scratch Resistant Matte or Glossy Varnish Star with glossy varnish Happy with matte finish Black Suit with efinish Desert Sand with matte nium Low Step Alloy 28" 5 AZX-581 1.5" SHIS With ock 150° Integrated Cables ANO Steps E6100 60Nm 1h 36V - Integrated on Downtube ovable to 100km hours total charge time ANO SC-E6100	M (52cm) - L (56cm) Approx. 20kg 150kg Powder painting scratch resistant with Glossy Varnish Metallic Blue Aluminium High Step Rigid Alloy 28" Semi integrated 1-1/8" BAFANG H400B Rear Wheel 45Nm 36V 360Wh - Integrated on Downtube - Non Removable 40km to 100km - 2A - 5 hours total charge time	with Matte or Glossy Varnish	Aluminium High Step Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm
nation of the products that ar on this website without prior , including equipment, ications, models, colors and rials. 46cm) - L/XL (54cm) IX. 26,5kg Per Painting Scratch Resistant Matte or Glossy Varnish Star with glossy varnish Happy with matte finish Black Suit with efinish Desert Sand with matte Inium Low Step Alloy 28" 5 AZX-581 1.5" SHIS With ock 150° Integrated Cables ANO Steps E6100 60Nm 1h 36V - Integrated on Downtube ovable to 100km hours total charge time	Approx. 20kg 150kg Powder painting scratch resistant with Glossy Varnish Metallic Blue Aluminium High Step Rigid Alloy 28" Semi integrated 1-1/8" BAFANG H400B Rear Wheel 45Nm 36V 360Wh - Integrated on Downtube - Non Removable 40km to 100km - 2A - 5 hours total charge time	Approx. 28kg 120kg Powder Painting Scratch Resistant with Matte or Glossy Varnish White Star with glossy varnish Happy Blue with matte finish Black Suit with matte finish Aluminium Low Step Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE C ALU 50Nm 504Wh 36V - Integrated on Downtube - Removable 40km to 100km	information of the products that appear on this website without prior notice, including equipment, specifications, models, colors and materials M (50cm) - L (56cm) Approx. 27kg 120kg - White Star with glossy varnish Happy, Blue with matte finish Black Suit with matte finish Black Suit with matte finish Aluminium High Step Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm 504Wh 36V - Semi-integrated on Downtube - Removable
nation of the products that ar on this website without prior , including equipment, ications, models, colors and rials. 46cm) - L/XL (54cm) IX. 26,5kg Per Painting Scratch Resistant Matte or Glossy Varnish Star with glossy varnish Happy with matte finish Black Suit with efinish Desert Sand with matte Inium Low Step Alloy 28" 5 AZX-581 1.5" SHIS With ock 150° Integrated Cables ANO Steps E6100 60Nm 1h 36V - Integrated on Downtube ovable to 100km hours total charge time	Approx. 20kg 150kg Powder painting scratch resistant with Glossy Varnish Metallic Blue Aluminium High Step Rigid Alloy 28" Semi integrated 1-1/8" BAFANG H400B Rear Wheel 45Nm 36V 360Wh - Integrated on Downtube - Non Removable 40km to 100km - 2A - 5 hours total charge time	Approx. 28kg 120kg Powder Painting Scratch Resistant with Matte or Glossy Varnish White Star with glossy varnish Happy Blue with matte finish Black Suit with matte finish Aluminium Low Step Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE C ALU 50Nm 504Wh 36V - Integrated on Downtube - Removable 40km to 100km	information of the products that appear on this website without prior notice, including equipment, specifications, models, colors and materials M (50cm) - L (56cm) Approx. 27kg 120kg - White Star with glossy varnish Happy Blue with matte finish Black Suit with matte finish Black Suit with matte finish Aluminium High Step Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm 504Wh 36V - Semi-integrated on Downtube - Removable
ar on this website without prior to including equipment, including equipment	Approx. 20kg 150kg Powder painting scratch resistant with Glossy Varnish Metallic Blue Aluminium High Step Rigid Alloy 28" Semi integrated 1-1/8" BAFANG H400B Rear Wheel 45Nm 36V 360Wh - Integrated on Downtube - Non Removable 40km to 100km - 2A - 5 hours total charge time	Approx. 28kg 120kg Powder Painting Scratch Resistant with Matte or Glossy Varnish White Star with glossy varnish Happy Blue with matte finish Black Suit with matte finish Aluminium Low Step Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE C ALU 50Nm 504Wh 36V - Integrated on Downtube - Removable 40km to 100km	appear on this website without prior notice, including equipment, specifications, models, colors and materials M (50cm) - L (56cm) Approx. 27kg 120kg - White Star with glossy varnish Happ Blue with matte finish Black Suit with matte finish Black Suit with matte finish Aluminium High Step Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm 504Wh 36V - Semi-integrated on Downtube - Removable
including equipment, ications, models, colors and rials. 46cm) - L/XL (54cm) x. 26,5kg er Painting Scratch Resistant Matte or Glossy Varnish Star with glossy varnish Happy with matte finish Black Suit with of finish Desert Sand with matte nium Low Step Alloy 28" 5 AZX-581 1.5" SHIS With ock 150° Integrated Cables AND Steps E6100 60Nm th 36V - Integrated on Downtube ovable to 100km	Approx. 20kg 150kg Powder painting scratch resistant with Glossy Varnish Metallic Blue Aluminium High Step Rigid Alloy 28" Semi integrated 1-1/8" BAFANG H400B Rear Wheel 45Nm 36V 360Wh - Integrated on Downtube - Non Removable 40km to 100km - 2A - 5 hours total charge time	Approx. 28kg 120kg Powder Painting Scratch Resistant with Matte or Glossy Varnish White Star with glossy varnish Happy Blue with matte finish Black Suit with matte finish Aluminium Low Step Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE C ALU 50Nm 504Wh 36V - Integrated on Downtube - Removable 40km to 100km	notice, including equipment, specifications, models, colors and materials M (50cm) - L (56cm) Approx. 27kg 120kg - White Star with glossy varnish Happ Blue with matte finish Black Suit with matte finish Black Suit with matte finish Aluminium High Step Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm 504Wh 36V - Semi-integrated on Downtube - Removable
ications, models, colors and rials. 46cm) - L/XL (54cm) x. 26,5kg er Painting Scratch Resistant Matte or Glossy Varnish Star with glossy varnish Happy with matte finish Black Suit with efinish Desert Sand with matte nium Low Step Alloy 28" 5 AZX-581 1.5" SHIS With ock 150° Integrated Cables ANO Steps E6100 60Nm th 36V - Integrated on Downtube ovable to 100km	Approx. 20kg 150kg Powder painting scratch resistant with Glossy Varnish Metallic Blue Aluminium High Step Rigid Alloy 28" Semi integrated 1-1/8" BAFANG H400B Rear Wheel 45Nm 36V 360Wh - Integrated on Downtube - Non Removable 40km to 100km - 2A - 5 hours total charge time	Approx. 28kg 120kg Powder Painting Scratch Resistant with Matte or Glossy Varnish White Star with glossy varnish Happy Blue with matte finish Black Suit with matte finish Aluminium Low Step Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE C ALU 50Nm 504Wh 36V - Integrated on Downtube - Removable 40km to 100km	specifications, models, colors and materials M (50cm) - L (56cm) Approx. 27kg 120kg - White Star with glossy varnish Happe Blue with matte finish Black Suit with matte finish Aluminium High Step Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm 504Wh 36V - Semi-integrated on Downtube - Removable
rials. 46cm) - L/XL (54cm) x. 26,5kg er Painting Scratch Resistant Matte or Glossy Varnish Star with glossy varnish Happy with matte finish Black Suit with e finish Desert Sand with matte nium Low Step Alloy 28" 5 AZX-58115" SHIS With ock 150° Integrated Cables ANO Steps E6100 60Nm th 36V - Integrated on Downtube ovable to 100km hours total charge time	Approx. 20kg 150kg Powder painting scratch resistant with Glossy Varnish Metallic Blue Aluminium High Step Rigid Alloy 28" Semi integrated 1-1/8" BAFANG H400B Rear Wheel 45Nm 36V 360Wh - Integrated on Downtube - Non Removable 40km to 100km - 2A - 5 hours total charge time	Approx. 28kg 120kg Powder Painting Scratch Resistant with Matte or Glossy Varnish White Star with glossy varnish Happy Blue with matte finish Black Suit with matte finish Aluminium Low Step Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE C ALU 50Nm 504Wh 36V - Integrated on Downtube - Removable 40km to 100km	materials M (50cm) - L (56cm) Approx. 27kg 120kg - White Star with glossy varnish Happy, Blue with matte finish Black Suit with matte finish Aluminium High Step Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm 504Wh 36V - Semi-integrated on Downtube - Removable
x. 26,5kg er Painting Scratch Resistant datte or Glossy Varnish Star with glossy varnish Happy with matte finish Black Suit with e finish Desert Sand with matte nium Low Step Alloy 28" 5 AZX-581 1.5" SHIS With ock 150° Integrated Cables ANO Steps E6100 60Nm th 36V - Integrated on Downtube ovable to 100km hours total charge time	Approx. 20kg 150kg Powder painting scratch resistant with Glossy Varnish Metallic Blue Aluminium High Step Rigid Alloy 28" Semi integrated 1-1/8" BAFANG H400B Rear Wheel 45Nm 36V 360Wh - Integrated on Downtube - Non Removable 40km to 100km - 2A - 5 hours total charge time	Approx. 28kg 120kg Powder Painting Scratch Resistant with Matte or Glossy Varnish White Star with glossy varnish Happy Blue with matte finish Black Suit with matte finish Aluminium Low Step Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE C ALU 50Nm 504Wh 36V - Integrated on Downtube - Removable 40km to 100km	Approx. 27kg 120kg - White Star with glossy varnish Happy, Blue with matte finish Black Suit with matte finish Aluminium High Step Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm 504Wh 36V - Semi-integrated on Downtube - Removable
x. 26,5kg er Painting Scratch Resistant datte or Glossy Varnish Star with glossy varnish Happy with matte finish Black Suit with e finish Desert Sand with matte nium Low Step Alloy 28" 5 AZX-581 1.5" SHIS With ock 150° Integrated Cables ANO Steps E6100 60Nm th 36V - Integrated on Downtube ovable to 100km hours total charge time	Approx. 20kg 150kg Powder painting scratch resistant with Glossy Varnish Metallic Blue Aluminium High Step Rigid Alloy 28" Semi integrated 1-1/8" BAFANG H400B Rear Wheel 45Nm 36V 360Wh - Integrated on Downtube - Non Removable 40km to 100km - 2A - 5 hours total charge time	Approx. 28kg 120kg Powder Painting Scratch Resistant with Matte or Glossy Varnish White Star with glossy varnish Happy Blue with matte finish Black Suit with matte finish Aluminium Low Step Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE C ALU 50Nm 504Wh 36V - Integrated on Downtube - Removable 40km to 100km	Approx. 27kg 120kg - White Star with glossy varnish Happy, Blue with matte finish Black Suit with matte finish Aluminium High Step Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm 504Wh 36V - Semi-integrated on Downtube - Removable
er Painting Scratch Resistant Matte or Glossy Varnish Star with glossy varnish Happy with matte finish Black Suit with e finish Desert Sand with matte nium Low Step Alloy 28" 5 AZX-58115" SHIS With ock 150° Integrated Cables ANO Steps E6100 60Nm th 36V - Integrated on Downtube ovable to 100km	Powder painting scratch resistant with Glossy Varnish Metallic Blue Aluminium High Step Rigid Alloy 28" Semi integrated 1-1/8" BAFANG H400B Rear Wheel 45Nm 36V 360Wh - Integrated on Downtube - Non Removable 40km to 100km - 2A - 5 hours total charge time	Powder Painting Scratch Resistant with Matte or Glossy Varnish White Star with glossy varnish Happy Blue with matte finish Black Suit with matte finish Aluminium Low Step Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE C ALU 50Nm 504Wh 36V - Integrated on Downtube - Removable 40km to 100km	- White Star with glossy varnish Happy, Blue with matte finish Black Suit with matte finish Aluminium High Step Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm 504Wh 36V - Semi-integrated on Downtube - Removable
er Painting Scratch Resistant Matte or Glossy Varnish Star with glossy varnish Happy with matte finish Black Suit with e finish Desert Sand with matte nium Low Step Alloy 28" 5 AZX-58115" SHIS With ock 150° Integrated Cables ANO Steps E6100 60Nm th 36V - Integrated on Downtube ovable to 100km hours total charge time	Powder painting scratch resistant with Glossy Varnish Metallic Blue Aluminium High Step Rigid Alloy 28" Semi integrated 1-1/8" BAFANG H400B Rear Wheel 45Nm 36V 360Wh - Integrated on Downtube - Non Removable 40km to 100km - 2A - 5 hours total charge time	Powder Painting Scratch Resistant with Matte or Glossy Varnish White Star with glossy varnish Happy Blue with matte finish Black Suit with matte finish Aluminium Low Step Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE C ALU 50Nm 504Wh 36V - Integrated on Downtube - Removable 40km to 100km	- White Star with glossy varnish Happy, Blue with matte finish Black Suit with matte finish Aluminium High Step Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm 504Wh 36V - Semi-integrated on Downtube - Removable
Matte or Glossy Varnish Star with glossy varnish Happy with matte finish Black Suit with of finish Desert Sand with matte nium Low Step Alloy 28" 5 AZX-581 1.5" SHIS With ock 150° Integrated Cables ANO Steps E6100 60Nm th 36V - Integrated on Downtube ovable to 100km hours total charge time	Glossy Varnish Metallic Blue Aluminium High Step Rigid Alloy 28" Semi integrated 1-1/8" BAFANG H400B Rear Wheel 45Nm 36V 360Wh - Integrated on Downtube - Non Removable 40km to 100km - 2A - 5 hours total charge time	with Matte or Glossy Varnish White Star with glossy varnish Happy Blue with matte finish Black Suit with matte finish Aluminium Low Step Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE C ALU 50Nm 504Wh 36V - Integrated on Downtube - Removable 40km to 100km	Blue with matte finish Black Suit with matte finish Aluminium High Step Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm 504Wh 36V - Semi-integrated on Downtube - Removable
Star with glossy varnish Happy with matte finish Black Suit with e finish Desert Sand with matte nium Low Step Alloy 28" 5 AZX-581 1.5" SHIS With cock 150° Integrated Cables ANO Steps E6100 60Nm th 36V - Integrated on Downtube ovable to 100km hours total charge time	Aluminium High Step Rigid Alloy 28" Semi integrated 1-1/8" BAFANG H400B Rear Wheel 45Nm 36V 360Wh - Integrated on Downtube - Non Removable 40km to 100km - 2A - 5 hours total charge time	White Star with glossy varnish Happy Blue with matte finish Black Suit with matte finish Aluminium Low Step Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE C ALU 50Nm 504Wh 36V - Integrated on Downtube - Removable 40km to 100km	Blue with matte finish Black Suit with matte finish Aluminium High Step Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm 504Wh 36V - Semi-integrated on Downtube - Removable
with matte finish Black Suit with efinish Desert Sand with matte nium Low Step Alloy 28" 5 AZX-581 1.5" SHIS With cock 150° Integrated Cables ANO Steps E6100 60Nm th 36V - Integrated on Downtube ovable to 100km hours total charge time	Aluminium High Step Rigid Alloy 28" Semi integrated 1-1/8" BAFANG H400B Rear Wheel 45Nm 36V 360Wh - Integrated on Downtube - Non Removable 40km to 100km - 2A - 5 hours total charge time	Blue with matte finish Black Suit with matte finish Aluminium Low Step Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE C ALU 50Nm 504Wh 36V - Integrated on Downtube - Removable 40km to 100km	Blue with matte finish Black Suit with matte finish Aluminium High Step Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm 504Wh 36V - Semi-integrated on Downtube - Removable
e finish Desert Sand with matte nium Low Step Alloy 28" 5 AZX-5811.5" SHIS With ock 150° Integrated Cables ANO Steps E6100 60Nm fh 36V - Integrated on Downtube ovable to 100km hours total charge time	Aluminium High Step Rigid Alloy 28" Semi integrated 1-1/8" BAFANG H400B Rear Wheel 45Nm 36V 360Wh - Integrated on Downtube - Non Removable 40km to 100km - 2A - 5 hours total charge time	matte finish Aluminium Low Step Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE C ALU 50Nm 504Wh 36V - Integrated on Downtube - Removable 40km to 100km	matte finish Aluminium High Step Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm 504Wh 36V - Semi-integrated on Downtube - Removable
nium Low Step Alloy 28" 5 AZX-581 1.5" SHIS With ock 150° Integrated Cables ANO Steps E6100 60Nm In 36V - Integrated on Downtube ovable to 100km hours total charge time	Rigid Alloy 28" Semi integrated 1-1/8" BAFANG H400B Rear Wheel 45Nm 36V 360Wh - Integrated on Downtube - Non Removable 40km to 100km - 2A - 5 hours total charge time	Aluminium Low Step Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE C ALU 50Nm 504Wh 36V - Integrated on Downtube - Removable 40km to 100km	Aluminium High Step Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm 504Wh 36V - Semi-integrated on Downtube - Removable
Alloy 28" 5 AZX-581 1.5" SHIS With ock 150° Integrated Cables AND Steps E6100 60Nm 1h 36V - Integrated on Downtube ovable to 100km hours total charge time	Rigid Alloy 28" Semi integrated 1-1/8" BAFANG H400B Rear Wheel 45Nm 36V 360Wh - Integrated on Downtube - Non Removable 40km to 100km - 2A - 5 hours total charge time	Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE C ALU 50Nm 504Wh 36V - Integrated on Downtube - Removable 40km to 100km	Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm 504Wh 36V - Semi-integrated on Downtube - Removable
Alloy 28" 5 AZX-581 1.5" SHIS With ock 150° Integrated Cables AND Steps E6100 60Nm 1h 36V - Integrated on Downtube ovable to 100km hours total charge time	Rigid Alloy 28" Semi integrated 1-1/8" BAFANG H400B Rear Wheel 45Nm 36V 360Wh - Integrated on Downtube - Non Removable 40km to 100km - 2A - 5 hours total charge time	Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE C ALU 50Nm 504Wh 36V - Integrated on Downtube - Removable 40km to 100km	Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm 504Wh 36V - Semi-integrated on Downtube - Removable
Alloy 28" 5 AZX-581 1.5" SHIS With ock 150° Integrated Cables AND Steps E6100 60Nm 1h 36V - Integrated on Downtube ovable to 100km hours total charge time	Rigid Alloy 28" Semi integrated 1-1/8" BAFANG H400B Rear Wheel 45Nm 36V 360Wh - Integrated on Downtube - Non Removable 40km to 100km - 2A - 5 hours total charge time	Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE C ALU 50Nm 504Wh 36V - Integrated on Downtube - Removable 40km to 100km	Rigid Alloy 28" FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm 504Wh 36V - Semi-integrated on Downtube - Removable
S AZX-581 1.5" SHIS With ock 150° Integrated Cables AND Steps E6100 60Nm fh 36V - Integrated on Downtube ovable to 100km hours total charge time	Semi integrated 1-1/8" BAFANG H400B Rear Wheel 45Nm 36V 360Wh - Integrated on Downtube - Non Removable 40km to 100km - 2A - 5 hours total charge time	FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE C ALU 50Nm 504Wh 36V - Integrated on Downtube - Removable 40km to 100km	FSA 1.5" to 1-1/8" Tapered SHIS BROSE DRIVE S ALU 90Nm 504Wh 36V - Semi-integrated on Downtube - Removable
ANO Steps E6100 60Nm 1h 36V - Integrated on Downtube ovable to 100km hours total charge time	BAFANG H400B Rear Wheel 45Nm 36V 360Wh - Integrated on Downtube - Non Removable 40km to 100km - 2A - 5 hours total charge time	BROSE DRIVE C ALU 50Nm 504Wh 36V - Integrated on Downtube - Removable 40km to 100km	BROSE DRIVE S ALU 90Nm 504Wh 36V - Semi-integrated on Downtube - Removable
ANO Steps E6100 60Nm fn 36V - Integrated on Downtube ovable to 100km hours total charge time	36V 360Wh - Integrated on Downtube - Non Removable 40km to 100km - 2A - 5 hours total charge time	504Wh 36V - Integrated on Downtube - Removable 40km to 100km	504Wh 36V - Semi-integrated on Downtube - Removable
fn 36V - Integrated on Downtube ovable to 100km hours total charge time	36V 360Wh - Integrated on Downtube - Non Removable 40km to 100km - 2A - 5 hours total charge time	504Wh 36V - Integrated on Downtube - Removable 40km to 100km	504Wh 36V - Semi-integrated on Downtube - Removable
fn 36V - Integrated on Downtube ovable to 100km hours total charge time	36V 360Wh - Integrated on Downtube - Non Removable 40km to 100km - 2A - 5 hours total charge time	504Wh 36V - Integrated on Downtube - Removable 40km to 100km	504Wh 36V - Semi-integrated on Downtube - Removable
ovable to 100km hours total charge time	- Non Removable 40km to 100km - 2A - 5 hours total charge time	- Removable 40km to 100km	Downtube - Removable
to 100km hours total charge time	40km to 100km - 2A - 5 hours total charge time	40km to 100km	
hours total charge time	- 2A - 5 hours total charge time		40km to 100km
		Yes	
			Yes
ANO SC-E6100	DAFANC DDC11	2A - 7 hours total charge time	4A - 3 to 6 hours total charge time
	BAFANG DP.C11	BROSE Allround	BROSE Allround
	700M Creval / 00mm / 21 0mm / Flave		
Omm / 31.8mm (Curved)	Z00M Gravel 400mm / 31.8mm / Flare 25°	AL 660mm / 31.8mm (Curved)	AL 680mm / 31.8mm (Straight)
mm - adjustable 0-90° - with	AL 100mm - 31.8mm - 7°	AL 90mm - 31.8mm - adjustable 0-	AL 90mm - 31.8mm - adjustable 0-
ated cables	CELLE ITALIA CO T	900	90°
N GP1	SELLE ITALIA SG Tape	ERGON GP1	ERGON GA30
INENTAL Contact Urban		CONTINENTAL Contact Cruiser	CONTINENTAL Double Fighter III
2,2"	VII TURIA Terreno Dry 29"X1,75"	28"x2,2"	29''x2,0''
	29"	28"	29"
Double Wall 25mm	Allov Double Wall 25mm	Alloy Double Wall 25mm	Alloy Double Wall 25mm
	·		Black Stainless Steel
			SHIMANO HB-MT400 100 Thru-axle
1	Alloy 9x135mm QR		15mm
	BAFANG H400B 135mm		SHIMANO Deore M6000 135mm
110 11c/(d3 30 00001 0B	D/1/11(01)11(00) 13311111	STILL DATE HEART SE COUCE OF	311111111111111111111111111111111111111
	TEVTDO Cable Activated Undraudia		
ANO Hydraulic MT200	•	SHIMANO Hydraulic MT200	SHIMANO Hydraulic MT200
ANO SM-DT10 190mm		SHIMANO SM-DT10 190mm	SHIMANO SM-RT10 180mm
HINO 2M-K I TO TROWW		PHIMANA PM-KI TA TRAMM	SHIMANO SM-RT10 180mm
		-	SHIMANO Deore 10S
		-	SHIMANO Deore 10S 11-42T
			SHIMANO Deore 10S
ANO SM-CRE61 38T	MIRANDA ChainFlow BCD104 38T	MIRANDA BCD 104 38T	SAMOX BCD 104 36T
ANO FC-E6100 175mm	MIRANDA JIS 170	SAMOX Shape 175/0	SAMOX Shape 175/0
ANO CN-NX10	KMC e10 Turbo e-bike series	SHIMANO CN-NX10	SHIMANO CN-E6090
HEBIE	Yes - MIRANDA	Yes - HEBIE	Yes - FSA
NVELO Tour AVS (may · 25Kg)	-	ATRANVELO Tour AVS (may · 25kg)	ATRANVELO Tour AVS (max.: 25Kg)
			AXA Blueline 30 with reflector
	-		PICCADILLY with reflector
NVELO Dux	-	ATRANVELO Dux	ATRANVELO Dux
	-	SKS	SKS
	-	Yes	Yes
cluded. Sold separately.	Not included. Sold separately.	Not included. Sold separately.	Not included. Sold separately.
ROYAL Rio Gel	SELLE ITALIA Model X Superflow	SELLE ROYAL Rio Gel	SELLE ROYAL Essenza Moderate Gel
	AL Black 300mm 31,6mm /15mm	AL Black 350mm 31,6mm/15mm	AL Black 350mm 31,6mm/15mm
rck 300mm 31 6mm/15mm	Alloy black with screw	Alloy black with quick release	Alloy black with quick release
ock 300mm 31,6mm/15mm	CHANGE THE PARTY OF THE PARTY O		Wiley plack with drick release
ick 300mm 31,6mm/15mm plack with quick release J SP-827 Flat with reflectors	MARWI SP-400 Flat with reflectors	UNION SP-827 Flat with reflectors	UNION SP-827 Flat with reflectors
	Double Wall 25mm Stainless Steel ANO HB-MT400 100 Thru-axle ANO Nexus SG-C6001-8D ANO Hydraulic MT200 ANO SM-RT10 180mm ANO WELL STEEL STE	29" 29" 29" Alloy Double Wall 25mm Stainless Steel ANO HB-MT400 100 Thru-axle ANO Nexus SG-C6001-8D BAFANG H400B 135mm TEKTRO Cable Activated Hydraulic HD-C705 ANO SM-RT10 180mm SHIMANO SM-RT26 180mm MICROSHIFT AdventX 10S MICRO	28"x2,2" 29" 28"x2,2" 29" 28"x2,2" 29" 28" 3800 Mel 25mm 3810y Double Wall 25mm 3810y PM 29135mm QR 3810y PM

^{*} We reserve the right to modify product information that appears on this website without prior notice, including equipment, specifications, models, colors and materials.