







PRODUCT INFORMATION			
FRAME SIZES	S-M (42cm) - L/XL (46cm)	S (45cm) - M (50cm) - L (55cm)	S-M (42cm) - L/XL (46cm)
WEIGHT	Approx. 26Kg	Approx. 28kg	Approx. 26Kg
MAXIMUM BIKE & RIDER WEIGHT	135Kg	120kg	135Kg
	Powder Painting Scratch Resistant with Matte	Powder Painting Scratch Resistant with Matte or	· ·
PAINTING	Varnish	Glossy Varnish	Varnish
COLOUR(s)	-	White Star with glossy varnish Happy Blue with matte finish Black Suit with matte finish	Black Fog with matte finish Pure Red with matte finish Rock Blue with matte finish
FRAME			
RAME	MTB Hardtail Aluminium	Aluminium Low Step	MTB Hardtail Aluminum
SUSPENSION	Rockshox 35S Air Travel 120mm Axle Boost 110mm 27.5"/29"	-	Rockshox 35S Air Travel 120mm Axle Boost 110mm 27.5"/29"
FORK	-	Rigid Alloy 28"	-
HEADSET	FSA 1.5" to 1-1/8" Tapered SHIS	FSA 1.5" to 1-1/8" Tapered SHIS	FSA 1.5" to 1-1/8" Tapered SHIS
E-BIKE SYSTEM			
DRIVE UNIT	BROSE DRIVE S MAG Horizontal 90Nm	BROSE DRIVE C ALU 50Nm	BROSE DRIVE S MAG Horizontal 90Nm
ATTERY	522Wh 36V - Integrated on Downtube - Removable	504Wh 36V - Integrated on Downtube - Removable	522Wh 36V - Integrated on Downtube - Removable
RANGE	40km to 100km	40km to 100km	40km to 100km
BATTERY LOCK KEY	Yes	Yes	Yes
CHARGER	4A - 3,6 hours total charge time	2A - 7 hours total charge time	4A - 3 to 6 hours total charge time
DISPLAY	BROSE Allround	BROSE Allround	Brose Allround
COCKPIT			
IANDLEBAR	FSA V-Drive 740mm / 31.8mm (Straight)	AL 660mm / 31.8mm (Curved)	FSA V-Drive 740mm / 31.8mm (Straight)
TEM	FSA V-Drive 60mm/ 31.8mm / ±6°	AL 90mm - 31.8mm - adjustable 0-90°	FSA V-Drive 60mm/ 31.8mm / ±6°
RIPS	ERGON GA30	ERGON GP1	ERGON GA30
VHEELSET	ENGON GASO	EROON OF 1	EROUN OASO
YRES	MAXXIS Rekon S - 27,5"x2,6" / M - L/XL- 29"x2,4"	CONTINENTAL Contact Cruiser 28"x2,2"	MAXXIS Rekon S - 27,5"x2,6" / M - L/XL- 29"x2,4
WHEEL SIZE	27,5" (S) / 29" (M-L/XL)	28"	27,5" (S) / 29" (M-L/XL)
RIMS	Alloy Double Wall 30mm (Tubeless Ready)	Alloy Double Wall 25mm	Alloy Double Wall 30mm (Tubeless Ready)
SPOKES	Black Stainless Steel	Black Stainless Steel	Black Stainless Steel
RONT HUB	SHIMANO HB-MT400-B Boost 110 Thru-axle 15mm	SHIMANO HB-MT400 100 Thru-axle 15mm	SHIMANO HB-MT400-B Boost 110 Thru-axle 15mm
REAR HUB	SHIMANO HB-MT400-B Boost 148 Thru-axle 12mm	SHIMANO Nexus SG-C6001-8D	SHIMANO HB-MT400-B Boost 148 Thru-axle 12mm
DRIVETRAIN & BRAKES			
BRAKES	SHIMANO Hydraulic MT400	SHIMANO Hydraulic MT200	SHIMANO Hydraulic MT400
BRAKE ROTOR - Front	SHIMANO SM-RT30 203mm	SHIMANO SM-RT10 180mm	SHIMANO SM-RT30 203mm
RAKE ROTOR - Rear	SHIMANO SM-RT30 180mm	SHIMANO SM-RT10 180mm	SHIMANO SM-RT30 180mm
REAR DERRAILEUR	SRAM NX 11S	-	SRAM NX 11S
ASSETTE	SRAM Power Glid 1130 11-42	-	SRAM Power Glid 1130 11-42
HIFTERS	SRAM NX 11S	SHIMANO Nexus 8	SRAM NX 11S
CHAINRING	MIRANDA ChainFlow 3D BCD104 38T	MIRANDA BCD 104 38T	MIRANDA ChainFlow 3D BCD104 38T
RANK	SAMOX Shape 170/0	SAMOX Shape 175/0	SAMOX Shape 170/0
HAIN	KMC E11 Turbo e-bike series	SHIMANO CN-NX10	KMC E11 Turbo e-bike series
HAINGUARD	Yes - FSA	Yes - HEBIE	Yes - FSA
SAFETY & ACESSORIES			
ACK	-	ATRANVELO Tour AVS (max.: 25Kg)	ATRANVELO Tour AVS (max.: 25Kg)
RONT LIGHT	-	AXA Blueline 30 with reflector	SPANNINGA Axendo 40 with reflector
EAR LIGHT	-	PICCADILLY with reflector	PICCADILY with reflector
CICKSTAND	-	ATRANVELO Dux	ATRANVELO Dux
1UDGUARD	-	SKS	SKS
BELL	-	Yes	Yes
BOTTLE CAGE	Not included. Sold separately.	Not included. Sold separately.	Not included. Sold separately.
ADDLE	SELLE SAN MARCO X3 e-bike	SELLE ROYAL Rio Gel	SELLE SAN MARCO X3 e-bike black
EAT POST	FSA Gossamer 31.6mm / 350mm /20mm	AL Black 350mm 31,6mm/15mm	FSA Gossamer 31.6mm / 350mm /20mm
SEAT CLAMP	Alloy black with screw	Alloy black with quick release	Alloy black with screw
	·		•
PEDALS	UNION SP-400 Flat with reflectors	UNION SP-827 Flat with reflectors	UNION SP-400 Flat with reflectors
FRAMELOCK	Not included. Sold separately.	Not included. Sold separately.	Not included. Sold separately.

 $^{^{\}star}$ We reserve the right to modify product information that appears on this website without prior notice, including equipment, specifications, models, colors and materials.