







n) - L/XL (46cm) ikg inting Scratch Resistant with Matte with matte finish Pure Red with sh Rock Blue with matte finish tail Aluminum 85S Air Travel 120mm Axle Boost 25'/29" 1-1/8" Tapered SHIS
inting Scratch Resistant with Matte with matte finish Pure Red with sh Rock Blue with matte finish tail Aluminum 35S Air Travel 120mm Axle Boost 7.5"/29"
with matte finish Pure Red with sh Rock Blue with matte finish tail Aluminum 35S Air Travel 120mm Axle Boost 7.5"/29"
with matte finish Pure Red with sh Rock Blue with matte finish tail Aluminum 35S Air Travel 120mm Axle Boost 7.5"/29"
tail Aluminum 35S Air Travel 120mm Axle Boost 7.5"/29"
95S Air Travel 120mm Axle Boost 7.5"/29"
95S Air Travel 120mm Axle Boost 7.5"/29"
7.5"/29"
1-1/8" Tapered SHIS
IVE S MAG Horizontal 90Nm
V - Integrated on Downtube - e
00km
hours total charge time
und
e 740mm / 31.8mm (Straight)
e 60mm/ 31.8mm / ±6°
30
kon S - 27,5''x2,6'' / M - L/XL- 29''x2,4'
29" (M-L/XL)
le Wall 30mm (Tubeless Ready)
nless Steel
HB-MT400-B Boost 110 Thru-axle
HB-MT400-B Boost 148 Thru-axle
Hydraulic MT400
SM-RT30 203mm
SM-RT30 180mm
.1S
er Glid 1130 11-42
1S
ChainFlow 3D BCD104 38T
ape 170/0
urbo e-bike series
0 Tour AVS (max.: 25Kg)
A Axendo 40 with reflector
with reflector
0 Dux
ed. Sold separately.
I MARCO X3 e-bike black
mer 31.6mm / 350mm /20mm
with screw
400 Flat with reflectors
ed. Sold separately.

^{*} We reserve the right to modify product information that appears on this website without prior notice, including equipment, specifications, models, colors and materials.