







PRODUCT INFORMATION			
NOTE	-	We reserve the right to modify the information of the products that appear on this website without prior notice, including equipment, specifications, models, colors and materials.	-
FRAME SIZES	M (52cm) - L (56cm)	S/M (46cm) - L/XL (54cm)	S (45cm) - M (50cm) - L (55cm)
WEIGHT	Approx. 20kg	Approx. 26,5kg	Approx. 28kg
MAXIMUM BIKE & RIDER WEIGHT	150kg	145kg	120kg
PAINTING	Powder painting scratch resistant with Glossy Varnish	Powder Painting Scratch Resistant with Matte or Glossy Varnish	Powder Painting Scratch Resistant with Matte or Glossy Varnish
COLOUR(s)	Metallic Blue	White Star with glossy varnish   Happy Blue with matte finish   Black Suit with matte finish   Desert Sand with matte finish	White Star with glossy varnish   Happy Blue with matte finish   Black Suit with matte finish
FRAME		Desert Sand With Matte Milish	
FRAME	Aluminium High Step	Aluminium Low Step	Aluminium Low Step
FORK	Rigid Alloy 28"	Rigid Alloy 28"	Rigid Alloy 28"
HEADSET	Semi integrated 1-1/8"	ACROS AZX-581 1.5" SHIS With Blocklock 150° Integrated Cables	FSA 1.5" to 1-1/8" Tapered SHIS
E-BIKE SYSTEM			
DRIVE UNIT	BAFANG H400B Rear Wheel 45Nm	SHIMANO Steps E6100 60Nm	BROSE DRIVE C ALU 50Nm
BATTERY	36V 360Wh - Integrated on Downtube - Non Removable	504Wh 36V - Integrated on Downtube - Removable	504Wh 36V - Integrated on Downtube - Removable
RANGE	40km to 100km	40km to 100km	40km to 100km
BATTERY LOCK KEY	-	Yes	Yes
CHARGER	2A - 5 hours total charge time	2A - 7 hours total charge time	2A - 7 hours total charge time
DISPLAY	BAFANG DP.C11	SHIMANO SC-E6100	BROSE Allround
COCKPIT			
HANDLEBAR	Z00M Gravel 400mm / 31.8mm / Flare 25°	AL 660mm / 31.8mm (Curved)	AL 660mm / 31.8mm (Curved)
STEM	AL 100mm - 31.8mm - 7°	AL 90mm - adjustable 0-90° - with integrated cables	AL 90mm - 31.8mm - adjustable 0-90°
GRIPS	SELLE ITALIA SG Tape	ERGON GP1	ERGON GP1
WHEELSET	·		
TYRES	VITTORIA Terreno Dry 29"x1,75"	CONTINENTAL Contact Urban 28"x2,2"	CONTINENTAL Contact Cruiser 28"x2,2"
WHEEL SIZE	29"	28"	28"
RIMS	Alloy Double Wall 25mm	Alloy Double Wall 25mm	Alloy Double Wall 25mm
SPOKES	Stainless Steel	Black Stainless Steel	Black Stainless Steel
FRONT HUB	Alloy 9x135mm QR	SHIMANO HB-MT400 100 Thru-axle 15mm	SHIMANO HB-MT400 100 Thru-axle 15mm
REAR HUB	BAFANG H400B 135mm	SHIMANO Nexus SG-C6001-8D	SHIMANO Nexus SG-C6001-8D
DRIVETRAIN & BRAKES			
BRAKES	TEKTRO Cable Activated Hydraulic HD-C705	SHIMANO Hydraulic MT200	SHIMANO Hydraulic MT200
BRAKE ROTOR - Front	SHIMANO SM-RT26 180mm	SHIMANO SM-RT10 180mm	SHIMANO SM-RT10 180mm
BRAKE ROTOR - Rear	SHIMANO SM-RT26 180mm	SHIMANO SM-RT10 180mm	SHIMANO SM-RT10 180mm
REAR DERRAILEUR	MICROSHIFT AdventX 10S	-	-
CASSETTE	MICROSHIFT AdventX 10S 11-48T	-	-
SHIFTERS	MICROSHIFT AdventX 10S	SHIMANO Nexus 8	SHIMANO Nexus 8
CHAINRING	MIRANDA ChainFlow BCD104 38T	SHIMANO SM-CRE61 38T	MIRANDA BCD 104 38T
CRANK	MIRANDA JIS 170	SHIMANO FC-E6100 175mm	SAMOX Shape 175/0
CHAIN	KMC e10 Turbo e-bike series	SHIMANO CN-NX10	SHIMANO CN-NX10
CHAINGUARD	Yes - MIRANDA	Yes - HEBIE	Yes - HEBIE
SAFETY & ACESSORIES			
RACK	-	ATRANVELO Tour AVS (max.: 25Kg)	ATRANVELO Tour AVS (max.: 25Kg)
FRONT LIGHT	-	SPANNINGA Axendo 40 with reflector	AXA Blueline 30 with reflector
REAR LIGHT	-	PICCADILLY with reflector	PICCADILLY with reflector
KICKSTAND	-	ATRANVELO Dux	ATRANVELO Dux
MUDGUARD	-	SKS	SKS
BELL	-	Yes	Yes
BOTTLE CAGE	Not included. Sold separately.	Not included. Sold separately.	Not included. Sold separately.
SADDLE	SELLE ITALIA Model X Superflow	SELLE ROYAL Rio Gel	SELLE ROYAL Rio Gel
SEAT POST	AL Black 300mm 31,6mm /15mm	AL Black 300mm 31,6mm/15mm	AL Black 350mm 31,6mm/15mm
SEAT CLAMP	Alloy black with screw	Alloy black with quick release	Alloy black with quick release
PEDALS	MARWI SP-400 Flat with reflectors	UNION SP-827 Flat with reflectors	UNION SP-827 Flat with reflectors
FRAMELOCK	Not included. Sold separately.	AXA Block XXL	Not included. Sold separately.
	1 /		, ,

<sup>\*</sup> We reserve the right to modify product information that appears on this website without prior notice, including equipment, specifications, models, colors and materials.