



E850 Trekking Low Step
€ 2,699



C500 Urban Motion
€ 2,299



C800 Trekking
€ 2,199



B400 Urban Low Step
€ 1,899

PRODUCT INFORMATION

NOTE	-	-	We reserve the right to modify the information of the products that appear on this website without prior notice, including equipment, specifications, models, colors and materials	-
FRAME SIZES	S/M (46cm) - L/XL (54cm)	M (44cm) - L (48cm)	M (50cm) - L (56cm)	S (46cm) - M (52cm) - L (56cm)
WEIGHT	26,5kg	Approx. 25kg	Approx. 27kg	Approx. 24kg
MAXIMUM BIKE & RIDER WEIGHT	145kg	120kg	120kg	145kg
PAINTING	-	Powder Painting Scratch Resistant with Matte or Glossy Varnish	-	Powder Painting Scratch Resistant With Matte Varnish
COLOUR(s)	White Star with glossy finish Black Suit with matte finish Desert Sand with matte finish	White Star with glossy varnish Happy Blue with matte finish Black Suit with matte finish	White Star with glossy varnish Happy Blue with matte finish Black Suit with matte finish	Moon Grey with matte finish Desert Sand with matte finish

FRAME

FRAME	Aluminium Low Step	Aluminium Low Step	Aluminium High Step	Aluminium Low Step
SUSPENSION	Sr Suntour Mobie E25 Air 75mm	-	-	-
FORK	-	Rigid Alloy 28"	Rigid Alloy 28"	Rigid Alloy 28"
HEADSET	ACROS AZX-581 1.5" SHIS With Blocklock 150° Integrated Cables	Acros 1.5" to 1-1/8" Tapered SHIS	FSA 1.5" to 1-1/8" Tapered SHIS	SHIS 1-1/8"

E-BIKE SYSTEM

DRIVE UNIT	SHIMANO Steps E6100 60Nm	SHIMANO STEPS E5000 40Nm	BROSE DRIVE S ALU 90Nm	BAFANG H400B Rear Wheel 45Nm
BATTERY	504Wh 36V - Integrated on Downtube - Removable	418Wh 36V - Semi-integrated in downtube - Removable	504Wh 36V - Semi-integrated on Downtube - Removable	360Wh 36V - Integrated on Downtube - Non Removable
RANGE	40km to 100km	40km to 100km	40km to 100km	40km to 100km
BATTERY LOCK KEY	Yes	Yes	Yes	-
CHARGER	2A - 7 hours total charge time	2A - 6 hours total charge time	4A - 3 to 6 hours total charge time	2A - 5 hours total charge time
DISPLAY	SHIMANO SC-E6100	SHIMANO SC-E6100	BROSE Allround	BAFANG DPC11

COCKPIT

HANDLEBAR	AL 680mm / 31.8mm (Straight)	AL 660mm / 31.8mm (Curved)	AL 680mm / 31.8mm (Straight)	AL 660mm / 31.8mm (Curved)
STEM	AL 90mm - adjustable 0-90° - with integrated cables	AL 90mm - 31.8mm - adjustable 0-90°	AL 90mm - 31.8mm - adjustable 0-90°	AL 90mm - 31.8mm - adjustable 0-90°
GRIPS</				