



M700 Wild

SKU	EBM700HTPRM
EAN	5608554016147
SIZE	M
AVAILABLE SIZES	M S L/XL
COLOR	PURE RED
AVAILABLE COLORS	ROCK BLUE , PURE RED , BLACK FOG



POWER

Let the robust performance of the BROSE DRIVE S MAG motor boasting an impressive 90Nm of torque propel you forward, opening a world of thrilling adventures and new horizons to explore. Embrace the excitement of discovering what awaits you on the other side of that next mountain.



CONTROL

Experience superior bike control with the advanced features of this e-bike. The built-in central motor with cadence, torque, and speed sensors ensures precise and responsive performance. Combined with the sturdy aluminum frame, efficient air suspension, and reliable SHIMANO MT400 hydraulic brakes, you can confidently conquer any terrain with ease.



COMFORT

Enjoy your ride to the fullest with the details of this e-bike, from the frame geometry that provides stability, to the tires with excellent grip, and the air suspension that smoothes out the terrain irregularities!



AUTONOMY

Experience the convenience of traveling from 40km up to 100km on a single battery charge with assisted riding, thanks to the efficient BROSE DRIVE S MAG Motor. Estimated autonomy depending on user's weight, road conditions or altitude range.

PRODUCT INFORMATION

PAINTING
Powder Painting Scratch Resistant with Matte Varnish
FRAME SIZES
S-M (42cm) - L/XL (46cm)
MAXIMUM BIKE & RIDER WEIGHT
135Kg
WEIGHT
Approx. 26Kg

FRAME

FRAME
MTB Hardtail Aluminium
SUSPENSION
Rockshox 35S Air Travel 120mm Axle Boost 110mm 27.5"/29"
HEADSET
FSA 1.5" to 1-1/8" Tapered SHIS

E-BIKE SYSTEM

DRIVE UNIT
BROSE DRIVE S MAG Horizontal 90Nm
BATTERY
522Wh 36V - Integrated on Downtube - Removable
RANGE
40km to 100km
BATTERY LOCK KEY
Yes
CHARGER
4A - 3,6 hours total charge time
DISPLAY
BROSE Allround

COCKPIT

HANDLEBAR
FSA V-Drive 740mm / 31.8mm (Straight)
STEM
FSA V-Drive 60mm/ 31.8mm / ±6°
GRIPS
ERGON GA30

WHEELSET

TYRES
MAXXIS Rekon S - 27,5"x2,6" / M - L/XL- 29"x2,4"
WHEEL SIZE
27,5" (S) / 29" (M-L/XL)
RIMS
Alloy Double Wall 30mm (Tubeless Ready)
SPOKES
Black Stainless Steel
FRONT HUB
SHIMANO HB-MT400-B Boost 110 Thru-axle 15mm
REAR HUB
SHIMANO HB-MT400-B Boost 148 Thru-axle 12mm

DRIVETRAIN & BRAKES


BRAKES
SHIMANO Hydraulic MT400
BRAKE ROTOR - FRONT
SHIMANO SM-RT30 203mm
BRAKE ROTOR - REAR
SHIMANO SM-RT30 180mm
REAR DERRAILEUR
SRAM NX 11S

CASSETTE
SRAM Power Glid 1130 11-42
SHIFTERS
SRAM NX 11S
CHAINRING
MIRANDA ChainFlow 3D BCD104 38T
CRANK
SAMOX Shape 170/0
CHAIN
KMC E11 Turbo e-bike series
CHAINGUARD
Yes - FSA

SAFETY & ACESSORIES

BOTTLE CAGE
Not included. Sold separately.
SADDLE
SELLE SAN MARCO X3 e-bike
SEAT POST
FSA Gossamer 31.6mm / 350mm /20mm
SEAT CLAMP
Alloy black with screw
PEDALS
UNION SP-400 Flat with reflectors
FRAMELOCK
Not included. Sold separately.

A	Seat Tube Length
	Top Tube Length
B	Top Tube Horizontal
C	Head Tube
D	Chain Stays
E	Head Tube Angle
F	Seat Tube Angle
G	Wheelbase
H	Reach
J	Stack



Note: The following numbers are for reference only. Correct air pressure must be adjusted by the individual rider while checking the sag.  
RIDER WEIGHT AIR SETTING <63 Kg 100-120 psi 63-72 Kg 120-135 psi 72-81 Kg 135-150 psi 81-90 Kg 150-170 psi >90 Kg 170+\* psi

\*do not exceed 265 psi